

BILL OF MATERIAL ONE 36" FIB

MARK	NO REQ'D	DIMENSION					LENGTH
		"a"	"b"	"c"	"d"	"e"	
A0401	X	3'-8"	---	---	---	---	3'-8"
A0402	X	7'-0"	---	---	---	---	7'-0"
A0501	20	12'-0"	---	---	---	---	12'-0"
A0601	16	2'-7"	---	---	---	---	2'-7"
N0501	X	10"	X'-X"	10"	---	---	X'-X"
N0502	X	10"	2'-9"	10"	---	---	4'-5"
N0601	8	1'-0"	X'-X"	1'-0"	---	---	X'-X"
N0602	8	1'-0"	2'-9"	1'-0"	---	---	4'-9"
RD0301	X	2'-0"	3 1/4"	10"	1'-3"	4 1/2"	4'-5"
VA0301	X	6 3/4"	11 3/4"	7 3/4"	8 1/2"	---	3'-2"
U0501	X	2'-2"	4"	---	---	---	4'-8"

QUANTITIES


ITEM	UNIT	ONE BEAM
CONCRETE, f'c X,XXX	CY	XXXX.X
REINFORCING STEEL	LB	XXXX
0.6" Ø L.R. STRANDS	LF	XXXX
STRUCTURAL STEEL	LS	AS NECESSARY

DESIGN DATA

STRANDS:
 0.6" Ø LOW RELAXATION GRADE 270
 AREA=0.217 SQ. IN.
 TENSIONING LOAD = 43.9 KIPS


CONCRETE:
 f'c =X.X KSI
 f'ci =X.X KSI

- REINFORCEMENT STEEL
- FULLY BONDED STRANDS
- ① FULLY BONDED STRANDS TO BE EXTENDED
- ② DEBONDED STRANDS FOR 'X'-'X' FROM END OF BEAM
- ③ DEBONDED STRANDS FOR 'X'-'X' FROM END OF BEAM



SIDE ELEVATION
 SHOWING REINFORCING STEEL, SOLE PLATE & DIAPHRAGM HOLES NOT SHOWN FOR CLARITY.


- ① SEE "FLORIDA I-BEAM GENERAL DETAILS" SHEET FOR PRESTRESSED STRAND BENDING DETAILS.
- ② ALTERNATE ADJACENT LEG OF N05 AND N06 BARS. SEE SECTION A-A.
- ③ SPACE WITH N0501 AND N0601.
- ④ ALTERNATE N0501 AND N0502.
- ⑤ N0501 OR N0601.
- ⑥ N0502 OR N0602.



STRAND LAYOUT
 X - STRAIGHT STRANDS
 X - DEBONDED STRANDS
 X - DRAPED STRANDS


AT END OF BEAM

AT CENTER OF BEAM



SECTION THRU BEAM
 STRANDS NOT SHOWN FOR CLARITY.

THIS DRAWING IS FURNISHED FOR INFORMATION ONLY. ALL DIMENSIONS SHOWN ARE SHEET SPECIFIC. ANY USE OF THIS DESIGN AND DRAWING, INCLUDING DIMENSIONS, MUST BE CHECKED BY THE USER'S ENGINEER TO ENSURE DESIGN IS ADEQUATE FOR THE INTENDED USE. ALL DRAWINGS MUST BE SIGNED AND SEALED BY A SOUTH CAROLINA REGISTERED PROFESSIONAL ENGINEER WHEN USED.



CONSULTANT NAME/LOGO

SOUTH CAROLINA
 DEPARTMENT OF TRANSPORTATION

PRESTRESSED CONCRETE BEAM
36" FLORIDA I-BEAM SPAN X

COUNTY: ##### ROUTE: #####

Dylan.Danks 6/18/2024 10:08:55 AM 704-FIB.dgn

REV.	BY	CHK.	DATE	DESCRIPTION OF REVISION

REVIEWED	QUAN.	DR.	DMD	AEL	DATE
					04-24

BILL OF MATERIAL ONE 45" FIB

MARK	NO REQ'D	DIMENSION					LENGTH
		"a"	"b"	"c"	"d"	"e"	
A0401	X	3'-8"	---	---	---	---	3'-8"
A0402	X	7'-0"	---	---	---	---	7'-0"
A0501	22	12'-0"	---	---	---	---	12'-0"
A0601	16	3'-4"	---	---	---	---	3'-4"
N0501	X	10"	X'-X"	10"	---	---	X'-X"
N0502	X	10"	3'-6"	10"	---	---	5'-2"
N0601	8	1'-0"	X'-X"	1'-0"	---	---	X'-X"
N0602	8	1'-0"	3'-6"	1'-0"	---	---	5'-6"
RD0301	X	2'-0"	3 1/4"	10"	1'-3"	4 1/2"	4'-5"
VA0301	X	6 3/4"	11 1/2"	7 3/4"	8 1/2"	---	3'-2"
U0501	X	2'-11"	4"	---	---	---	6'-2"

QUANTITIES


ITEM	UNIT	ONE BEAM
CONCRETE, f'c X,XXX	CY	XXXX.X
REINFORCING STEEL	LB	XXXX
0.6" Ø L.R. STRANDS	LF	XXXX
STRUCTURAL STEEL	LS	AS NECESSARY

DESIGN DATA

STRANDS:
 0.6" Ø LOW RELAXATION GRADE 270
 AREA=0.217 SQ. IN.
 TENSIONING LOAD = 43.9 KIPS


CONCRETE:
 f'c =X.X KSI
 f'ci =X.X KSI

- REINFORCEMENT STEEL
- FULLY BONDED STRANDS
- △ FULLY BONDED STRANDS TO BE EXTENDED
- ◇ DEBONDED STRANDS FOR X'-X" FROM END OF BEAM
- ⊙ DEBONDED STRANDS FOR X'-X" FROM END OF BEAM




SIDE ELEVATION
 SHOWING REINFORCING STEEL, SOLE PLATE & DIAPHRAGM HOLES NOT SHOWN FOR CLARITY.


- ① SEE "FLORIDA I-BEAM GENERAL DETAILS" SHEET FOR PRESTRESSED STRAND BENDING DETAILS.
- ② ALTERNATE ADJACENT LEG OF N05 AND N06 BARS. SEE SECTION A-A.
- ③ SPACE WITH N0501 AND N0601.
- ④ ALTERNATE N0501 AND N0502.
- ⑤ N0501 OR N0601.
- ⑥ N0502 OR N0602.



STRAND LAYOUT
 AT END OF BEAM
 AT CENTER OF BEAM



SECTION THRU BEAM
 STRANDS NOT SHOWN FOR CLARITY.



SECTION A-A
 SHOWING BARS N0501, N0502, N0601, N0602 & A0601 ONLY.

THIS DRAWING IS FURNISHED FOR INFORMATION ONLY. ALL DIMENSIONS SHOWN ARE SHEET SPECIFIC. ANY USE OF THIS DESIGN AND DRAWING, INCLUDING DIMENSIONS, MUST BE CHECKED BY THE USER'S ENGINEER TO ENSURE DESIGN IS ADEQUATE FOR THE INTENDED USE. ALL DRAWINGS MUST BE SIGNED AND SEALED BY A SOUTH CAROLINA REGISTERED PROFESSIONAL ENGINEER WHEN USED.

CONSULTANT NAME/LOGO

SOUTH CAROLINA
 DEPARTMENT OF TRANSPORTATION

PRESTRESSED CONCRETE BEAM
45" FLORIDA I-BEAM SPAN X

COUNTY: ##### ROUTE: #####

Dylan Danks 6/18/2024 10:08:56 AM 704-FIB.dgn

REV.	BY	CHK.	DATE	DESCRIPTION OF REVISION

REVIEWED	QUAN.	DR.	DMD	AEL	DATE

X - STRAIGHT STRANDS
 X - DEBONDED STRANDS
 X - DRAPED STRANDS

BILL OF MATERIAL ONE 54" FIB

MARK	NO REQ'D	DIMENSION					LENGTH
		"a"	"b"	"c"	"d"	"e"	
A0401	X	3'-8"					3'-8"
A0402	X	7'-0"					7'-0"
A0501	26	12'-0"					12'-0"
A0601	16	4'-1"					4'-1"
N0501	X	10"	X'-X"	10"			X'-X"
N0502	X	10"	4'-3"	10"			5'-11"
N0601	8	1'-0"	X'-X"	1'-0"			X'-X"
N0602	8	1'-0"	4'-3"	1'-0"			6'-3"
RD0301	X	2'-0"	3 1/4"	10"	1'-3"	4 1/2"	4'-5"
VA0301	X	6 3/4"	11 1/2"	7 3/4"	8 1/2"		3'-2"
U0501	X	3'-8"	4"				7'-8"

QUANTITIES


ITEM	UNIT	ONE BEAM
CONCRETE, f'c XXX	CY	XXXX.X
REINFORCING STEEL	LB	XXXX
0.6" Ø L.R. STRANDS	LF	XXXX
STRUCTURAL STEEL	LS	AS NECESSARY

DESIGN DATA

STRANDS:
 0.6" Ø LOW RELAXATION GRADE 270
 AREA=0.217 SQ. IN.
 TENSIONING LOAD = 43.9 KIPS

CONCRETE:
 f'c =X.X KSI
 f'ci =X.X KSI


- REINFORCEMENT STEEL
- FULLY BONDED STRANDS
- △ FULLY BONDED STRANDS TO BE EXTENDED
- ◇ DEBONDED STRANDS FOR X'-X" FROM END OF BEAM
- ⊙ DEBONDED STRANDS FOR X'-X" FROM END OF BEAM



SIDE ELEVATION


SHOWING REINFORCING STEEL, SOLE PLATE & DIAPHRAGM HOLES NOT SHOWN FOR CLARITY.

- ① SEE "FLORIDA I-BEAM GENERAL DETAILS" SHEET FOR PRESTRESSED STRAND BENDING DETAILS.
- ② ALTERNATE ADJACENT LEG OF N05 AND N06 BARS. SEE SECTION A-A.
- ③ SPACE WITH N0501 AND N0601.
- ④ ALTERNATE N0501 AND N0502.
- ⑤ N0501 OR N0601.
- ⑥ N0502 OR N0602.




STRAND LAYOUT

X - STRAIGHT STRANDS
 X - DEBONDED STRANDS
 X - DRAPED STRANDS



SECTION THRU BEAM

STRANDS NOT SHOWN FOR CLARITY.



CONSULTANT NAME/LOGO

SOUTH CAROLINA DEPARTMENT OF TRANSPORTATION

PRESTRESSED CONCRETE BEAM
 54" FLORIDA I-BEAM SPAN X

THIS DRAWING IS FURNISHED FOR INFORMATION ONLY. ALL DIMENSIONS SHOWN ARE SHEET SPECIFIC. ANY USE OF THIS DESIGN AND DRAWING, INCLUDING DIMENSIONS, MUST BE CHECKED BY THE USER'S ENGINEER TO ENSURE DESIGN IS ADEQUATE FOR THE INTENDED USE. ALL DRAWINGS MUST BE SIGNED AND SEALED BY A SOUTH CAROLINA REGISTERED PROFESSIONAL ENGINEER WHEN USED.

REVIEWED	QUAN.	DR.	DES.	BY	CHK.	DATE

Dylan Danks 6/18/2024 10:08:57 AM 704-FIB.dgn

REV.	BY	CHK.	DATE	DESCRIPTION OF REVISION

BILL OF MATERIAL ONE 63" FIB

MARK	NO REQ'D	DIMENSION					LENGTH
		"a"	"b"	"c"	"d"	"e"	
A0401	X	3'-8"					3'-8"
A0402	X	7'-0"					7'-0"
A0501	28	12'-0"					12'-0"
A0601	16	4'-10"					4'-10"
N0501	X	10"	X'-X"	10"			X'-X"
N0502	X	10"	5'-0"	10"			6'-8"
N0601	8	1'-0"	X'-X"	1'-0"			X'-X"
N0602	8	1'-0"	5'-0"	1'-0"			7'-0"
RD0301	X	2'-0"	3 1/4"	10"	1'-3"	4 1/2"	4'-5"
VA0301	X	6 3/4"	11 1/2"	7 3/4"	8 1/2"		3'-2"
U0501	X	4'-5"	4"				9'-2"

QUANTITIES


ITEM	UNIT	ONE BEAM
CONCRETE, f'c X,XXX	CY	XXXX.X
REINFORCING STEEL	LB	XXXX
0.6" Ø L.R. STRANDS	LF	XXXX
STRUCTURAL STEEL	LS	AS NECESSARY

DESIGN DATA

STRANDS:
 0.6" Ø LOW RELAXATION GRADE 270
 AREA=0.217 SQ. IN.
 TENSIONING LOAD = 43.9 KIPS

CONCRETE:
 f'c = X.X KSI
 f'ci = X.X KSI


- REINFORCEMENT STEEL
- FULLY BONDED STRANDS
- △ FULLY BONDED STRANDS TO BE EXTENDED
- ◇ DEBONDED STRANDS FOR X'-X" FROM END OF BEAM
- ⊙ DEBONDED STRANDS FOR X'-X" FROM END OF BEAM



SIDE ELEVATION

SHOWING REINFORCING STEEL, SOLE PLATE & DIAPHRAGM HOLES NOT SHOWN FOR CLARITY.

- ① SEE "FLORIDA I-BEAM GENERAL DETAILS" SHEET FOR PRESTRESSED STRAND BENDING DETAILS.
- ② ALTERNATE ADJACENT LEG OF N05 AND N06 BARS. SEE SECTION A-A.
- ③ SPACE WITH N0501 AND N0601.
- ④ ALTERNATE N0501 AND N0502.
- ⑤ N0501 OR N0601.
- ⑥ N0502 OR N0602.




AT END OF BEAM

AT CENTER OF BEAM


STRAND LAYOUT

- X - STRAIGHT STRANDS
- X - DEBONDED STRANDS
- X - DRAPED STRANDS



SECTION THRU BEAM

STRANDS NOT SHOWN FOR CLARITY.



CONSULTANT NAME/LOGO

SOUTH CAROLINA DEPARTMENT OF TRANSPORTATION

PRESTRESSED CONCRETE BEAM
 63" FLORIDA I-BEAM SPAN X

THIS DRAWING IS FURNISHED FOR INFORMATION ONLY. ALL DIMENSIONS SHOWN ARE SHEET SPECIFIC. ANY USE OF THIS DESIGN AND DRAWING, INCLUDING DIMENSIONS, MUST BE CHECKED BY THE USER'S ENGINEER TO ENSURE DESIGN IS ADEQUATE FOR THE INTENDED USE. ALL DRAWINGS MUST BE SIGNED AND SEALED BY A SOUTH CAROLINA REGISTERED PROFESSIONAL ENGINEER WHEN USED.

COUNTY: #####

ROUTE: #####

DRAWING NUMBER: 704-FIB.63.SPXXX

REVIEWED	QUAN.	DR.	DES.	BY	CHK.	DATE

Dylan.Danks 6/18/2024 10:08:57 AM 704-FIB.dgn

REV.	BY	CHK.	DATE	DESCRIPTION OF REVISION

BILL OF MATERIAL ONE 72" FIB

MARK	NO REQ'D	DIMENSION					LENGTH
		"a"	"b"	"c"	"d"	"e"	
A0401	X	3'-8"					3'-8"
A0402	X	7'-0"					7'-0"
A0501	32	12'-0"					12'-0"
A0601	16	5'-7"					5'-7"
N0501	X	10"	X'-X"	10"			X'-X"
N0502	X	10"	5'-9"	10"			7'-5"
N0601	8	1'-0"	X'-X"	1'-0"			X'-X"
N0602	8	1'-0"	5'-9"	1'-0"			7'-9"
RD0301	X	2'-0"	3 1/4"	10"	1'-3"	4 1/2"	4'-5"
VA0301	X	6 3/4"	11 1/2"	7 3/4"	8 1/2"		3'-2"
U0501	X	5'-2"	4"				10'-8"

QUANTITIES


ITEM	UNIT	ONE BEAM
CONCRETE, f'c X,XXX	CY	XXXX.X
REINFORCING STEEL	LB	XXXX
0.6" Ø L.R. STRANDS	LF	XXXX
STRUCTURAL STEEL	LS	AS NECESSARY

DESIGN DATA

STRANDS:
0.6" Ø LOW RELAXATION GRADE 270
AREA=0.217 SQ. IN.
TENSIONING LOAD = 43.9 KIPS

CONCRETE:
f'c = X.X KSI
f'ci = X.X KSI


- REINFORCEMENT STEEL
- FULLY BONDED STRANDS
- △ FULLY BONDED STRANDS TO BE EXTENDED
- ◇ DEBONDED STRANDS FOR X'-X" FROM END OF BEAM
- ⊙ DEBONDED STRANDS FOR X'-X" FROM END OF BEAM



SIDE ELEVATION


SHOWING REINFORCING STEEL, SOLE PLATE & DIAPHRAGM HOLES NOT SHOWN FOR CLARITY.

- ① SEE "FLORIDA I-BEAM GENERAL DETAILS" SHEET FOR PRESTRESSED STRAND BENDING DETAILS.
- ② ALTERNATE ADJACENT LEG OF N05 AND N06 BARS. SEE SECTION A-A.
- ③ SPACE WITH N0501 AND N0601.
- ④ ALTERNATE N0501 AND N0502.
- ⑤ N0501 OR N0601.
- ⑥ N0502 OR N0602.




STRAND LAYOUT

X - STRAIGHT STRANDS
X - DEBONDED STRANDS
X - DRAPED STRANDS



SECTION THRU BEAM

STRANDS NOT SHOWN FOR CLARITY.



SECTION A-A

SHOWING BARS N0501, N0502, N0601, N0602 & A0601 ONLY.

Dylan Danks 6/18/2024 10:08:58 AM 704-FIB.dgn

REV.	BY	CHK.	DATE	DESCRIPTION OF REVISION

REVIEWED	QUAN.	DR.	DMD	AEL	04-24	BY	CHK.	DATE

THIS DRAWING IS FURNISHED FOR INFORMATION ONLY. ALL DIMENSIONS SHOWN ARE SHEET SPECIFIC. ANY USE OF THIS DESIGN AND DRAWING, INCLUDING DIMENSIONS, MUST BE CHECKED BY THE USER'S ENGINEER TO ENSURE DESIGN IS ADEQUATE FOR THE INTENDED USE. ALL DRAWINGS MUST BE SIGNED AND SEALED BY A SOUTH CAROLINA REGISTERED PROFESSIONAL ENGINEER WHEN USED.

CONSULTANT NAME/LOGO

SOUTH CAROLINA DEPARTMENT OF TRANSPORTATION

PRESTRESSED CONCRETE BEAM
72" FLORIDA I-BEAM SPAN X

COUNTY: #### ROUTE: ####

BILL OF MATERIAL ONE 84" FIB

MARK	NO REQ'D	DIMENSION					LENGTH
		"a"	"b"	"c"	"d"	"e"	
A0401	X	3'-8"					3'-8"
A0402	X	7'-0"					7'-0"
A0501	36	12'-0"					12'-0"
A0601	16	6'-7"					6'-7"
N0501	X	10"	X'-X"	10"			X'-X"
N0502	X	10"	6'-9"	10"			8'-5"
N0601	8	1'-0"	X'-X"	1'-0"			X'-X"
N0602	8	1'-0"	6'-9"	1'-0"			8'-9"
RD0301	X	2'-0"	3 1/4"	10"	1'-3"	4 1/2"	4'-5"
VA0301	X	6 3/4"	11 3/4"	7 3/4"	8 1/2"		3'-2"
U0501	X	6'-2"	4"				12'-8"

QUANTITIES


ITEM	UNIT	ONE BEAM
CONCRETE, f'c X,XXX	CY	XXXX.X
REINFORCING STEEL	LB	XXXX
0.6" Ø L.R. STRANDS	LF	XXXX
STRUCTURAL STEEL	LS	AS NECESSARY

DESIGN DATA

STRANDS:
 0.6" Ø LOW RELAXATION GRADE 270
 AREA=0.217 SQ. IN.
 TENSIONING LOAD = 43.9 KIPS

CONCRETE:
 f'c =X.X KSI
 f'ci =X.X KSI


- REINFORCEMENT STEEL
- FULLY BONDED STRANDS
- △ FULLY BONDED STRANDS TO BE EXTENDED
- ◇ DEBONDED STRANDS FOR X'-X" FROM END OF BEAM
- ⊗ DEBONDED STRANDS FOR X'-X" FROM END OF BEAM



SIDE ELEVATION

SHOWING REINFORCING STEEL, SOLE PLATE & DIAPHRAGM HOLES NOT SHOWN FOR CLARITY.

- ① SEE "FLORIDA I-BEAM GENERAL DETAILS" SHEET FOR PRESTRESSED STRAND BENDING DETAILS.
- ② ALTERNATE ADJACENT LEG OF N05 AND N06 BARS. SEE SECTION A-A.
- ③ SPACE WITH N0501 AND N0601.
- ④ ALTERNATE N0501 AND N0502.
- ⑤ N0501 OR N0601.
- ⑥ N0502 OR N0602.




SECTION A-A

SHOWING BARS N0501, N0502, N0601, N0602 & A0601 ONLY.


Dylan Danks 6/18/2024 10:08:59 AM 704-FIB.dgn

REV.	BY	CHK.	DATE	DESCRIPTION OF REVISION


REVIEWED	QUAN.	DR.	DMD	AEL	DATE



AT END OF BEAM



AT CENTER OF BEAM



SECTION THRU BEAM

STRANDS NOT SHOWN FOR CLARITY.

THIS DRAWING IS FURNISHED FOR INFORMATION ONLY. ALL DIMENSIONS SHOWN ARE SHEET SPECIFIC. ANY USE OF THIS DESIGN AND DRAWING, INCLUDING DIMENSIONS, MUST BE CHECKED BY THE USER'S ENGINEER TO ENSURE DESIGN IS ADEQUATE FOR THE INTENDED USE. ALL DRAWINGS MUST BE SIGNED AND SEALED BY A SOUTH CAROLINA REGISTERED PROFESSIONAL ENGINEER WHEN USED.

CONSULTANT NAME/LOGO


SOUTH CAROLINA DEPARTMENT OF TRANSPORTATION

PRESTRESSED CONCRETE BEAM
84" FLORIDA I-BEAM SPAN X

COUNTY: ##### ROUTE: #####

DRAWING NUMBER: 704-FIB.84.SPXXX

PAY LENGTH OF BEAM OUT TO OUT = X'-X"



SIDE ELEVATION

SHOWING REINFORCING STEEL, SOLE PLATE & DIAPHRAGM HOLES NOT SHOWN FOR CLARITY.

BILL OF MATERIAL ONE 96" FIB

MARK	NO REQ'D	DIMENSION					LENGTH
		"a"	"b"	"c"	"d"	"e"	
A0401	X	3'-8"					3'-8"
A0402	X	7'-0"					7'-0"
A0501	42	12'-0"					12'-0"
A0601	16	7'-7"					7'-7"
N0501	X	10"	X'-X"	10"			X'-X"
N0502	X	10"	7'-9"	10"			9'-5"
N0601	8	1'-0"	X'-X"	1'-0"			X'-X"
N0602	8	1'-0"	7'-9"	1'-0"			9'-9"
RD0301	X	2'-0"	3 1/4"	10"	1'-3"	4 1/2"	4'-5"
VA0301	X	6 3/4"	11 1/2"	7 3/4"	8 1/2"		3'-2"
U0501	X	7'-2"	4"				14'-8"

QUANTITIES


ITEM	UNIT	ONE BEAM
CONCRETE, f'c X,XXX	CY	XXXX.X
REINFORCING STEEL	LB	XXXX
0.6" Ø L.R. STRANDS	LF	XXXX
STRUCTURAL STEEL	LS	AS NECESSARY

DESIGN DATA


STRANDS:
 0.6" Ø LOW RELAXATION GRADE 270
 AREA=0.217 SQ. IN.
 TENSIONING LOAD = 43.9 KIPS

CONCRETE:
 f'c =X.X KSI
 f'ci =X.X KSI

- REINFORCEMENT STEEL
- FULLY BONDED STRANDS
- △ FULLY BONDED STRANDS TO BE EXTENDED
- ◇ DEBONDED STRANDS FOR X'-X" FROM END OF BEAM
- ⊗ DEBONDED STRANDS FOR X'-X" FROM END OF BEAM



STRAND LAYOUT




SECTION THRU BEAM

STRANDS NOT SHOWN FOR CLARITY.

- ① SEE "FLORIDA I-BEAM GENERAL DETAILS" SHEET FOR PRESTRESSED STRAND BENDING DETAILS.
- ② ALTERNATE ADJACENT LEG OF N05 AND N06 BARS. SEE SECTION A-A.
- ③ SPACE WITH N0501 AND N0601.
- ④ ALTERNATE N0501 AND N0502.
- ⑤ N0501 OR N0601.
- ⑥ N0502 OR N0602.

A0601 BUNDLED WITH N0601 OR N0602 (TYP.)



SECTION A-A

SHOWING BARS N0501, N0502, N0601, N0602 & A0601 ONLY.

Dylan Danks 6/18/2024 10:09:00 AM 704-FIB.dgn

REV.	BY	CHK.	DATE	DESCRIPTION OF REVISION

REVIEWED	QUAN.	DR.	DMD	AEL	DATE


THIS DRAWING IS FURNISHED FOR INFORMATION ONLY. ALL DIMENSIONS SHOWN ARE SHEET SPECIFIC. ANY USE OF THIS DESIGN AND DRAWING, INCLUDING DIMENSIONS, MUST BE CHECKED BY THE USER'S ENGINEER TO ENSURE DESIGN IS ADEQUATE FOR THE INTENDED USE. ALL DRAWINGS MUST BE SIGNED AND SEALED BY A SOUTH CAROLINA REGISTERED PROFESSIONAL ENGINEER WHEN USED.

CONSULTANT NAME/LOGO


SOUTH CAROLINA DEPARTMENT OF TRANSPORTATION

PRESTRESSED CONCRETE BEAM
96" FLORIDA I-BEAM SPAN X


COUNTY: ##### ROUTE: #####



INTERMEDIATE DIAPHRAGM HOLE LOCATION DETAIL



INTERMEDIATE DIAPHRAGM REINFORCEMENT DETAIL



SECTION B-B
SHOWING HOLES AND ADDITIONAL REINFORCING REQUIRED AT INTERMEDIATE DIAPHRAGMS.

BEAM CAMBERS & DEFLECTIONS					
BEAM CAMBER		DEFLECTION DUE TO			
AT RELEASE	* AT ERECTION	INTERIOR DIAPHRAGM	STAY-IN-PLACE FORMS **	SLAB	BARRIER PARAPET
X"	X"	X"	X"	X"	X"


* BASED ON A BEAM AGE OF 60 DAYS AT THE TIME OF ERECTION
 ** DEFLECTION DUE TO WEIGHT OF METAL FORMS AND THE WEIGHT OF THE CONCRETE IN THE FLUTES OF THE FORMS.
 "+" INDICATES UPWARD MOVEMENT
 "-" INDICATES DOWNWARD MOVEMENT

REV.	BY	CHK.	DATE	DESCRIPTION OF REVISION

REVIEWED	QUAN.	DR.	DMD	AEL	04-24

THIS DRAWING IS FURNISHED FOR INFORMATION ONLY. ALL DIMENSIONS SHOWN ARE SHEET SPECIFIC. ANY USE OF THIS DESIGN AND DRAWING, INCLUDING DIMENSIONS, MUST BE CHECKED BY THE USER'S ENGINEER TO ENSURE DESIGN IS ADEQUATE FOR THE INTENDED USE. ALL DRAWINGS MUST BE SIGNED AND SEALED BY A SOUTH CAROLINA REGISTERED PROFESSIONAL ENGINEER WHEN USED.


CONSULTANT NAME/LOGO	
SOUTH CAROLINA DEPARTMENT OF TRANSPORTATION	
FLORIDA I-BEAM DETAILS SPAN X - ALT 1	
COUNTY: ####	ROUTE: ####




INTERMEDIATE DIAPHRAGM HOLE LOCATION DETAIL

BEAM CAMBER		DEFLECTION DUE TO			
AT RELEASE	* AT ERECTION	INTERIOR DIAPHRAGM	STAY-IN-PLACE FORMS **	SLAB	BARRIER PARAPET
X"	X"	X"	X"	X"	X"

* BASED ON A BEAM AGE OF 60 DAYS AT THE TIME OF ERECTION
 ** DEFLECTION DUE TO WEIGHT OF METAL FORMS AND THE WEIGHT OF THE CONCRETE IN THE FLUTES OF THE FORMS.
 "+" INDICATES UPWARD MOVEMENT
 "-" INDICATES DOWNWARD MOVEMENT



INTERMEDIATE DIAPHRAGM REINFORCEMENT DETAIL



SECTION B-B
 SHOWING HOLES AND ADDITIONAL REINFORCING REQUIRED AT INTERMEDIATE DIAPHRAGMS.


Dylan.Danks 6/18/2024 10:09:02 AM 704_FIB.dgn

REV.	BY	CHK.	DATE	DESCRIPTION OF REVISION

REVIEWED	QUAN.	DR.	DMD	AEL	DATE

THIS DRAWING IS FURNISHED FOR INFORMATION ONLY. ALL DIMENSIONS SHOWN ARE SHEET SPECIFIC. ANY USE OF THIS DESIGN AND DRAWING, INCLUDING DIMENSIONS, MUST BE CHECKED BY THE USER'S ENGINEER TO ENSURE DESIGN IS ADEQUATE FOR THE INTENDED USE. ALL DRAWINGS MUST BE SIGNED AND SEALED BY A SOUTH CAROLINA REGISTERED PROFESSIONAL ENGINEER WHEN USED.


CONSULTANT NAME/LOGO	
SOUTH CAROLINA DEPARTMENT OF TRANSPORTATION	
FLORIDA I-BEAM DETAILS SPAN X - ALT 2	
COUNTY: ####	ROUTE: ####




INTERMEDIATE DIAPHRAGM HOLE LOCATION DETAIL

BEAM CAMBER		DEFLECTION DUE TO			
AT RELEASE	* AT ERECTION	INTERIOR DIAPHRAGM	STAY-IN-PLACE FORMS **	SLAB	BARRIER PARAPET
X"	X"	X"	X"	X"	X"

* BASED ON A BEAM AGE OF 60 DAYS AT THE TIME OF ERECTION
 ** DEFLECTION DUE TO WEIGHT OF METAL FORMS AND THE WEIGHT OF THE CONCRETE IN THE FLUTES OF THE FORMS.
 "+" INDICATES UPWARD MOVEMENT
 "-" INDICATES DOWNWARD MOVEMENT



INTERMEDIATE DIAPHRAGM REINFORCEMENT DETAIL




SECTION B-B
 SHOWING HOLES AND ADDITIONAL REINFORCING REQUIRED AT INTERMEDIATE DIAPHRAGMS.

REV.	BY	CHK.	DATE	DESCRIPTION OF REVISION

REVIEWED	QUAN.	DR.	DMD	AEL	04-24

THIS DRAWING IS FURNISHED FOR INFORMATION ONLY. ALL DIMENSIONS SHOWN ARE SHEET SPECIFIC. ANY USE OF THIS DESIGN AND DRAWING, INCLUDING DIMENSIONS, MUST BE CHECKED BY THE USER'S ENGINEER TO ENSURE DESIGN IS ADEQUATE FOR THE INTENDED USE. ALL DRAWINGS MUST BE SIGNED AND SEALED BY A SOUTH CAROLINA REGISTERED PROFESSIONAL ENGINEER WHEN USED.


CONSULTANT NAME/LOGO	
SOUTH CAROLINA DEPARTMENT OF TRANSPORTATION	
FLORIDA I-BEAM DETAILS SPAN X - ALT 3	
COUNTY: ####	ROUTE: ####




INTERMEDIATE DIAPHRAGM HOLE LOCATION DETAIL

BEAM CAMBER		DEFLECTION DUE TO			
AT RELEASE	* AT ERECTION	INTERIOR DIAPHRAGM	STAY-IN-PLACE FORMS **	SLAB	BARRIER PARAPET
X"	X"	X"	X"	X"	X"

* BASED ON A BEAM AGE OF 60 DAYS AT THE TIME OF ERECTION
 ** DEFLECTION DUE TO WEIGHT OF METAL FORMS AND THE WEIGHT OF THE CONCRETE IN THE FLUTES OF THE FORMS.
 "+" INDICATES UPWARD MOVEMENT
 "-" INDICATES DOWNWARD MOVEMENT



INTERMEDIATE DIAPHRAGM REINFORCEMENT DETAIL



SECTION B-B
 SHOWING HOLES AND ADDITIONAL REINFORCING REQUIRED AT INTERMEDIATE DIAPHRAGMS.


REV.	BY	CHK.	DATE	DESCRIPTION OF REVISION

REVIEWED	QUAN.	DR.	DMD	AEL	04-24

THIS DRAWING IS FURNISHED FOR INFORMATION ONLY. ALL DIMENSIONS SHOWN ARE SHEET SPECIFIC. ANY USE OF THIS DESIGN AND DRAWING, INCLUDING DIMENSIONS, MUST BE CHECKED BY THE USER'S ENGINEER TO ENSURE DESIGN IS ADEQUATE FOR THE INTENDED USE. ALL DRAWINGS MUST BE SIGNED AND SEALED BY A SOUTH CAROLINA REGISTERED PROFESSIONAL ENGINEER WHEN USED.

CONSULTANT NAME/LOGO	
SOUTH CAROLINA DEPARTMENT OF TRANSPORTATION	
FLORIDA I-BEAM DETAILS SPAN X - ALT 4	
COUNTY: ####	ROUTE: ####

Dylan.Danks 6/18/2024 10:09:03 AM 704_FIB.dgn




INTERMEDIATE DIAPHRAGM HOLE LOCATION DETAIL
INTERIOR BEAM SHOWN.


- ① OMIT THESE HOLES ON BEAM 1.
- ② OMIT THESE HOLES ON BEAM X.

BEAM CAMBER		DEFLECTION DUE TO			
AT RELEASE	* AT ERECTION	INTERIOR DIAPHRAGM	STAY-IN-PLACE FORMS **	SLAB	BARRIER PARAPET
X"	X"	X"	X"	X"	X"


* BASED ON A BEAM AGE OF 60 DAYS AT THE TIME OF ERECTION
 ** DEFLECTION DUE TO WEIGHT OF METAL FORMS AND THE WEIGHT OF THE CONCRETE IN THE FLUTES OF THE FORMS.
 "+" INDICATES UPWARD MOVEMENT
 "-" INDICATES DOWNWARD MOVEMENT



INTERMEDIATE DIAPHRAGM REINFORCEMENT DETAIL



SECTION B-B
SHOWING HOLES AND ADDITIONAL REINFORCING REQUIRED AT INTERMEDIATE DIAPHRAGMS.



TOP FLANGE CLIP DETAIL


Dylan.Danks 6/18/2024 10:09:03 AM 704_FIB.dgn

REV.	BY	CHK.	DATE	DESCRIPTION OF REVISION

REVIEWED	QUAN.	DR.	DMD	AEL	DATE

THIS DRAWING IS FURNISHED FOR INFORMATION ONLY. ALL DIMENSIONS SHOWN ARE SHEET SPECIFIC. ANY USE OF THIS DESIGN AND DRAWING, INCLUDING DIMENSIONS, MUST BE CHECKED BY THE USER'S ENGINEER TO ENSURE DESIGN IS ADEQUATE FOR THE INTENDED USE. ALL DRAWINGS MUST BE SIGNED AND SEALED BY A SOUTH CAROLINA REGISTERED PROFESSIONAL ENGINEER WHEN USED.

CONSULTANT NAME/LOGO	
SOUTH CAROLINA DEPARTMENT OF TRANSPORTATION	
FLORIDA I-BEAM DETAILS SPAN X - ALT 5	
COUNTY: ####	ROUTE: ####




INTERMEDIATE DIAPHRAGM HOLE LOCATION DETAIL

INTERIOR BEAM SHOWN.


- ① OMIT THESE HOLES ON BEAM 1.
- ② OMIT THESE HOLES ON BEAM X.

BEAM CAMBER		DEFLECTION DUE TO			
AT RELEASE	* AT ERECTION	INTERIOR DIAPHRAGM	STAY-IN-PLACE FORMS **	SLAB	BARRIER PARAPET
X"	X"	X"	X"	X"	X"


* BASED ON A BEAM AGE OF 60 DAYS AT THE TIME OF ERECTION
 ** DEFLECTION DUE TO WEIGHT OF METAL FORMS AND THE WEIGHT OF THE CONCRETE IN THE FLUTES OF THE FORMS.
 "+" INDICATES UPWARD MOVEMENT
 "-" INDICATES DOWNWARD MOVEMENT



INTERMEDIATE DIAPHRAGM REINFORCEMENT DETAIL



SECTION B-B
 SHOWING HOLES AND ADDITIONAL REINFORCING REQUIRED AT INTERMEDIATE DIAPHRAGMS.



TOP FLANGE CLIP DETAIL


REV.	BY	CHK.	DATE	DESCRIPTION OF REVISION

REVIEWED	QUAN.	DR.	DMD	AEL	04-24

THIS DRAWING IS FURNISHED FOR INFORMATION ONLY. ALL DIMENSIONS SHOWN ARE SHEET SPECIFIC. ANY USE OF THIS DESIGN AND DRAWING, INCLUDING DIMENSIONS, MUST BE CHECKED BY THE USER'S ENGINEER TO ENSURE DESIGN IS ADEQUATE FOR THE INTENDED USE. ALL DRAWINGS MUST BE SIGNED AND SEALED BY A SOUTH CAROLINA REGISTERED PROFESSIONAL ENGINEER WHEN USED.

CONSULTANT NAME/LOGO	
SOUTH CAROLINA DEPARTMENT OF TRANSPORTATION	
FLORIDA I-BEAM DETAILS SPAN X - ALT 6	
COUNTY: ####	ROUTE: ####

Dylan.Danks 6/18/2024 10:09:04 AM 704_FIB.dgn




INTERMEDIATE DIAPHRAGM HOLE LOCATION DETAIL
INTERIOR BEAM SHOWN.


- ① OMIT THESE HOLES ON BEAM 1.
- ② OMIT THESE HOLES ON BEAM X.

BEAM CAMBER		DEFLECTION DUE TO			
AT RELEASE	* AT ERECTION	INTERIOR DIAPHRAGM	STAY-IN-PLACE FORMS **	SLAB	BARRIER PARAPET
X"	X"	X"	X"	X"	X"


* BASED ON A BEAM AGE OF 60 DAYS AT THE TIME OF ERECTION
 ** DEFLECTION DUE TO WEIGHT OF METAL FORMS AND THE WEIGHT OF THE CONCRETE IN THE FLUTES OF THE FORMS.
 "+" INDICATES UPWARD MOVEMENT
 "-" INDICATES DOWNWARD MOVEMENT



INTERMEDIATE DIAPHRAGM REINFORCEMENT DETAIL



SECTION B-B
SHOWING HOLES AND ADDITIONAL REINFORCING REQUIRED AT INTERMEDIATE DIAPHRAGMS.



TOP FLANGE CLIP DETAIL


Dylan.Danks 6/18/2024 10:09:04 AM 704_FIB.dgn

REV.	BY	CHK.	DATE	DESCRIPTION OF REVISION

REVIEWED	QUAN.	DR.	DMD	AEL	DATE

THIS DRAWING IS FURNISHED FOR INFORMATION ONLY. ALL DIMENSIONS SHOWN ARE SHEET SPECIFIC. ANY USE OF THIS DESIGN AND DRAWING, INCLUDING DIMENSIONS, MUST BE CHECKED BY THE USER'S ENGINEER TO ENSURE DESIGN IS ADEQUATE FOR THE INTENDED USE. ALL DRAWINGS MUST BE SIGNED AND SEALED BY A SOUTH CAROLINA REGISTERED PROFESSIONAL ENGINEER WHEN USED.

CONSULTANT NAME/LOGO	
SOUTH CAROLINA DEPARTMENT OF TRANSPORTATION	
FLORIDA I-BEAM DETAILS SPAN X - ALT 7	
COUNTY: ####	ROUTE: ####




INTERMEDIATE DIAPHRAGM HOLE LOCATION DETAIL
INTERIOR BEAM SHOWN.


- ① OMIT THESE HOLES ON BEAM 1.
- ② OMIT THESE HOLES ON BEAM X.

BEAM CAMBER		DEFLECTION DUE TO			
AT RELEASE	* AT ERECTION	INTERIOR DIAPHRAGM	STAY-IN-PLACE FORMS **	SLAB	BARRIER PARAPET
X"	X"	X"	X"	X"	X"


* BASED ON A BEAM AGE OF 60 DAYS AT THE TIME OF ERECTION
 ** DEFLECTION DUE TO WEIGHT OF METAL FORMS AND THE WEIGHT OF THE CONCRETE IN THE FLUTES OF THE FORMS.
 "+" INDICATES UPWARD MOVEMENT
 "-" INDICATES DOWNWARD MOVEMENT



INTERMEDIATE DIAPHRAGM REINFORCEMENT DETAIL



SECTION B-B
SHOWING HOLES AND ADDITIONAL REINFORCING REQUIRED AT INTERMEDIATE DIAPHRAGMS.




TOP FLANGE CLIP DETAIL

REV.	BY	CHK.	DATE	DESCRIPTION OF REVISION

REVIEWED	QUAN.	DR.	DMD	AEL	04-24

THIS DRAWING IS FURNISHED FOR INFORMATION ONLY. ALL DIMENSIONS SHOWN ARE SHEET SPECIFIC. ANY USE OF THIS DESIGN AND DRAWING, INCLUDING DIMENSIONS, MUST BE CHECKED BY THE USER'S ENGINEER TO ENSURE DESIGN IS ADEQUATE FOR THE INTENDED USE. ALL DRAWINGS MUST BE SIGNED AND SEALED BY A SOUTH CAROLINA REGISTERED PROFESSIONAL ENGINEER WHEN USED.

CONSULTANT NAME/LOGO	
SOUTH CAROLINA DEPARTMENT OF TRANSPORTATION	
FLORIDA I-BEAM DETAILS SPAN X - ALT 8	
COUNTY: ####	ROUTE: ####




INTERMEDIATE DIAPHRAGM HOLE LOCATION DETAIL
INTERIOR BEAM SHOWN.


- ① OMIT THESE HOLES ON BEAM 1.
- ② OMIT THESE HOLES ON BEAM X.

BEAM CAMBER		DEFLECTION DUE TO			
AT RELEASE	* AT ERECTION	INTERIOR DIAPHRAGM	STAY-IN-PLACE FORMS **	SLAB	BARRIER PARAPET
X"	X"	X"	X"	X"	X"


* BASED ON A BEAM AGE OF 60 DAYS AT THE TIME OF ERECTION
 ** DEFLECTION DUE TO WEIGHT OF METAL FORMS AND THE WEIGHT OF THE CONCRETE IN THE FLUTES OF THE FORMS.
 "+" INDICATES UPWARD MOVEMENT
 "-" INDICATES DOWNWARD MOVEMENT



INTERMEDIATE DIAPHRAGM REINFORCEMENT DETAIL



SECTION B-B
SHOWING HOLES AND ADDITIONAL REINFORCING REQUIRED AT INTERMEDIATE DIAPHRAGMS.



TOP FLANGE CLIP DETAIL


Dylan Danks 6/18/2024 10:09:05 AM 704_FIB.dgn

REV.	BY	CHK.	DATE	DESCRIPTION OF REVISION

REVIEWED	QUAN.	DR.	DMD	AEL	DATE

THIS DRAWING IS FURNISHED FOR INFORMATION ONLY. ALL DIMENSIONS SHOWN ARE SHEET SPECIFIC. ANY USE OF THIS DESIGN AND DRAWING, INCLUDING DIMENSIONS, MUST BE CHECKED BY THE USER'S ENGINEER TO ENSURE DESIGN IS ADEQUATE FOR THE INTENDED USE. ALL DRAWINGS MUST BE SIGNED AND SEALED BY A SOUTH CAROLINA REGISTERED PROFESSIONAL ENGINEER WHEN USED.

CONSULTANT NAME/LOGO	
SOUTH CAROLINA DEPARTMENT OF TRANSPORTATION	
FLORIDA I-BEAM DETAILS SPAN X - ALT 9	
COUNTY: ####	ROUTE: ####



INTERMEDIATE DIAPHRAGM HOLE LOCATION DETAIL

INTERIOR BEAM SHOWN.

- ① OMIT THESE HOLES ON BEAM 1.
- ② OMIT THESE HOLES ON BEAM X.


BEAM CAMBERS & DEFLECTIONS

BEAM CAMBER		DEFLECTION DUE TO			
AT RELEASE	* AT ERECTION	INTERIOR DIAPHRAGM	STAY-IN-PLACE FORMS **	SLAB	BARRIER PARAPET
X"	X"	X"	X"	X"	X"


* BASED ON A BEAM AGE OF 60 DAYS AT THE TIME OF ERECTION

** DEFLECTION DUE TO WEIGHT OF METAL FORMS AND THE WEIGHT OF THE CONCRETE IN THE FLUTES OF THE FORMS.

"+" INDICATES UPWARD MOVEMENT
 "-." INDICATES DOWNWARD MOVEMENT




INTERMEDIATE DIAPHRAGM REINFORCEMENT DETAIL



SECTION B-B

SHOWING HOLES AND ADDITIONAL REINFORCING REQUIRED AT INTERMEDIATE DIAPHRAGMS.



TOP FLANGE CLIP DETAIL


Dylan.Danks 6/18/2024 10:09:01 AM 704_FIB.dgn

REV.	BY	CHK.	DATE	DESCRIPTION OF REVISION

REVIEWED	QUAN.	DR.	DMD	AEL	DATE

THIS DRAWING IS FURNISHED FOR INFORMATION ONLY. ALL DIMENSIONS SHOWN ARE SHEET SPECIFIC. ANY USE OF THIS DESIGN AND DRAWING, INCLUDING DIMENSIONS, MUST BE CHECKED BY THE USER'S ENGINEER TO ENSURE DESIGN IS ADEQUATE FOR THE INTENDED USE. ALL DRAWINGS MUST BE SIGNED AND SEALED BY A SOUTH CAROLINA REGISTERED PROFESSIONAL ENGINEER WHEN USED.

CONSULTANT NAME/LOGO	
SOUTH CAROLINA DEPARTMENT OF TRANSPORTATION	
FLORIDA I-BEAM DETAILS SPAN X - ALT 10	
COUNTY: ####	ROUTE: ####




INTERMEDIATE DIAPHRAGM HOLE LOCATION DETAIL
INTERIOR BEAM SHOWN.


- ① OMIT THESE HOLES ON BEAM 1.
- ② OMIT THESE HOLES ON BEAM X.

BEAM CAMBER		DEFLECTION DUE TO			
AT RELEASE	* AT ERECTION	INTERIOR DIAPHRAGM	STAY-IN-PLACE FORMS **	SLAB	BARRIER PARAPET
X"	X"	X"	X"	X"	X"


* BASED ON A BEAM AGE OF 60 DAYS AT THE TIME OF ERECTION
 ** DEFLECTION DUE TO WEIGHT OF METAL FORMS AND THE WEIGHT OF THE CONCRETE IN THE FLUTES OF THE FORMS.
 "+" INDICATES UPWARD MOVEMENT
 "-" INDICATES DOWNWARD MOVEMENT



INTERMEDIATE DIAPHRAGM REINFORCEMENT DETAIL



SECTION B-B
SHOWING HOLES AND ADDITIONAL REINFORCING REQUIRED AT INTERMEDIATE DIAPHRAGMS.



TOP FLANGE CLIP DETAIL


Dylan.Danks 6/18/2024 10:09:01 AM 704_FIB.dgn

REV.	BY	CHK.	DATE	DESCRIPTION OF REVISION

REVIEWED	QUAN.	DR.	DMD	AEL	DATE

THIS DRAWING IS FURNISHED FOR INFORMATION ONLY. ALL DIMENSIONS SHOWN ARE SHEET SPECIFIC. ANY USE OF THIS DESIGN AND DRAWING, INCLUDING DIMENSIONS, MUST BE CHECKED BY THE USER'S ENGINEER TO ENSURE DESIGN IS ADEQUATE FOR THE INTENDED USE. ALL DRAWINGS MUST BE SIGNED AND SEALED BY A SOUTH CAROLINA REGISTERED PROFESSIONAL ENGINEER WHEN USED.

CONSULTANT NAME/LOGO	
SOUTH CAROLINA DEPARTMENT OF TRANSPORTATION	
FLORIDA I-BEAM DETAILS SPAN X - ALT 11	
COUNTY: ####	ROUTE: ####




INTERMEDIATE DIAPHRAGM HOLE LOCATION DETAIL
INTERIOR BEAM SHOWN.


- ① OMIT THESE HOLES ON BEAM 1.
- ② OMIT THESE HOLES ON BEAM X.

BEAM CAMBER		DEFLECTION DUE TO			
AT RELEASE	* AT ERECTION	INTERIOR DIAPHRAGM	STAY-IN-PLACE FORMS **	SLAB	BARRIER PARAPET
X"	X"	X"	X"	X"	X"


* BASED ON A BEAM AGE OF 60 DAYS AT THE TIME OF ERECTION
 ** DEFLECTION DUE TO WEIGHT OF METAL FORMS AND THE WEIGHT OF THE CONCRETE IN THE FLUTES OF THE FORMS.
 "+" INDICATES UPWARD MOVEMENT
 "-" INDICATES DOWNWARD MOVEMENT



INTERMEDIATE DIAPHRAGM REINFORCEMENT DETAIL



SECTION B-B
SHOWING HOLES AND ADDITIONAL REINFORCING REQUIRED AT INTERMEDIATE DIAPHRAGMS.



TOP FLANGE CLIP DETAIL


REV.	BY	CHK.	DATE	DESCRIPTION OF REVISION

REVIEWED	QUAN.	DR.	DMD	AEL	04-24

THIS DRAWING IS FURNISHED FOR INFORMATION ONLY. ALL DIMENSIONS SHOWN ARE SHEET SPECIFIC. ANY USE OF THIS DESIGN AND DRAWING, INCLUDING DIMENSIONS, MUST BE CHECKED BY THE USER'S ENGINEER TO ENSURE DESIGN IS ADEQUATE FOR THE INTENDED USE. ALL DRAWINGS MUST BE SIGNED AND SEALED BY A SOUTH CAROLINA REGISTERED PROFESSIONAL ENGINEER WHEN USED.

CONSULTANT NAME/LOGO	
SOUTH CAROLINA DEPARTMENT OF TRANSPORTATION	
FLORIDA I-BEAM DETAILS SPAN X - ALT 12	
COUNTY: ####	ROUTE: ####


a	LENGTH	$\pm \frac{1}{4}$ " PER 25' LENGTH, ± 1 " MAX.
b	WIDTH (OVERALL)	$+\frac{3}{8}$ ", $-\frac{1}{4}$ "
b ₁	WEB WIDTH	$+\frac{3}{8}$ ", $-\frac{1}{4}$ "
c	DEPTH (OVERALL)	$+\frac{1}{2}$ ", $-\frac{1}{4}$ "
c ₁	FLANGE DEPTH	$\pm \frac{1}{4}$ "
d	VARIATION FROM SPECIFIED PLAN END SQUARENESS OR SKEW	$\pm \frac{1}{8}$ " PER 12" WIDTH, $\pm \frac{1}{2}$ " MAX.
e	VARIATION FROM SPECIFIED ELEVATION END SQUARENESS OR SKEW	$\pm \frac{3}{16}$ " PER 12" DEPTH, ± 1 " MAX.
f	SWEEP	$\frac{1}{8}$ " PER 10' LENGTH
g	CAMBER VARIATION FROM DESIGN CAMBER (MEASUREMENT OF CAMBER FOR COMPARISON TO PREDICTED DESIGN VALUES SHOULD BE COMPLETED WITHIN 72 HRS. OF TRANSFER OF PRESTR. FORCE)	$\pm \frac{1}{8}$ " PER 10' $\pm \frac{1}{2}$ " MAX. UP TO 80' LENGTH ± 1 " MAX. FOR LENGTH GREATER THAN 80'
h	LOCAL SMOOTHNESS OF ANY SURFACE	$\frac{1}{4}$ " IN 10'
k	LOCATION OF STRAND (INDIVIDUAL)	$\pm \frac{1}{4}$ "
	LOCATION OF STRAND (BUNDLED)	$\pm \frac{1}{2}$ "
k ₁	LOCATION OF HARP POINTS FOR HARPED STRANDS FROM DESIGN LOCATION	± 20 "
k ₂	LOCATION OF POST-TENSIONING DUCT	$\pm \frac{1}{4}$ "
l ₁	LOCATION OF EMBEDMENT	± 1 "
l ₂	TIPPING AND FLUSHNESS OF EMBEDMENT	$\pm \frac{1}{4}$ "
m ₁	LOCATION OF BEARING ASSEMBLY	$\pm \frac{5}{8}$ "
m ₂	TIPPING AND FLUSHNESS OF BEARING ASSEMBLY	$\pm \frac{1}{8}$ "
p	LOCATION OF INSERTS, SLEEVES, OR HOLES FOR STRUCTURAL CONNECTIONS	$\pm \frac{1}{2}$ "
q ₁	LOCATION OF HANDLING DEVICE PARALLEL TO LENGTH OF MEMBER	± 6 "
q ₂	LOCATION OF HANDLING DEVICE TRANSVERSE TO LENGTH OF MEMBER	± 1 "
s ₁	LONGITUDINAL SPACING OF STIRRUPS	± 2 "
s ₂	LONGITUDINAL SPACING OF STIRRUPS WITHIN DISTANCE "C" FROM MEMBER ENDS	± 1 "
s ₃	STIRRUP PROJECTION FROM BEAM SURFACE	$+\frac{1}{4}$ ", $-\frac{1}{2}$ "
s ₄	PRESTRESSING STRAND PROJECTION FROM BEAM END	$\pm \frac{1}{2}$ "



SECTION THROUGH SIDE OF BEAM

SECTION THROUGH END OF BEAM

SOLE PLATE DETAIL
 REINFORCING STEEL AND STRANDS NOT SHOWN.




PARTIAL ELEVATION AT END OF BEAM

SECTION C-C

① GROUTED RECESS AT END OF PRETENSIONED STRAND

① PROVIDE A 1" RECESS IN THE END OF THE BEAM, ONLY AT BEAM ENDS THAT ARE NOT PERMANENTLY ENCASED IN CONCRETE. CUT ALL STRANDS 1/2" BACK INTO RECESS AND FILL THE RECESS WITH AN EPOXY MORTAR ESPECIALLY FORMULATED FOR APPLICATIONS ON VERTICAL SURFACES.





SECTION AT END DIAPHRAGM

REINFORCEMENT AND EXPANSION JOINT DETAILS NOT SHOWN FOR CLARITY.

② USE APPROVED HOT-DIPPED GALVANIZED FERRULE INSERTS (1/2"-13 UNC) AND INSTALL IN ACCORDANCE WITH MANUFACTURER'S RECOMMENDATION. OMIT INSERTS ON OUTSIDE FACE OF EXTERIOR BEAM. ADJUST INSERT LOCATIONS AS NECESSARY TO AVOID REINFORCEMENT IN BEAM. INSTALL INSERTS PERPENDICULAR TO THE FACE OF THE WEB.

REVIEWED	QUAN.	DMD	AEL	04-24	BY	CHK.	DATE
DR.	DES.						

Dylan.Danks 6/18/2024 10:09:05 AM 704-FIB.dgn



PRESTRESSING STRAND BENDING DETAIL

THIS DRAWING IS FURNISHED FOR INFORMATION ONLY. ALL DIMENSIONS SHOWN ARE SHEET SPECIFIC. ANY USE OF THIS DESIGN AND DRAWING, INCLUDING DIMENSIONS, MUST BE CHECKED BY THE USER'S ENGINEER TO ENSURE DESIGN IS ADEQUATE FOR THE INTENDED USE. ALL DRAWINGS MUST BE SIGNED AND SEALED BY A SOUTH CAROLINA REGISTERED PROFESSIONAL ENGINEER WHEN USED.

NOTES:
 SEE SECTION 704 OF THE STANDARD SPECIFICATIONS FOR ADDITIONAL REQUIREMENTS AND INFORMATION REGARDING PRESTRESSED CONCRETE BEAMS. SHOP DRAWINGS MUST BE SUBMITTED IN ACCORDANCE WITH THE STANDARD SPECIFICATIONS.
 INCLUDE STRAND BENDING PROCEDURE IN SHOP PLANS.
 GALVANIZE ALL OVERHANG BRACKETS IN THE TOP FLANGE OF EXTERIOR BEAMS IN ACCORDANCE WITH AASHTO M 111, AASHTO M 232, OR ASTM F 2329 AS APPROPRIATE AND DETAIL ACCORDINGLY IN THE SHOP PLANS.
 USE PRESTRESSING STRANDS THAT CONFORM TO THE LATEST AASHTO M 203 FOR GRADE 270 (LOW RELAXATION).
 THE TENSIONING LOAD IN ALL 0.6" Ø LOW RELAXATION STRANDS IS 43.9 KIPS. DO NOT RELEASE THE STRANDS UNTIL THE COMPRESSIVE STRENGTH OF THE CONCRETE HAS REACHED THE VALUE SHOWN FOR f_{ci}.
 ON THE TOP SURFACE OF BEAMS WHERE CAST-IN-PLACE CONCRETE WILL BE PLACED, PROVIDE A FINISH THAT IS CLEAN, FREE OF LAITANCE, AND INTENTIONALLY ROUGHENED TO A FULL AMPLITUDE OF APPROXIMATELY 1/4". FINISH TOP OF BEAM LEVEL ACROSS WIDTH OF FLANGE.
 ALWAYS MAINTAIN PRESTRESSED CONCRETE BEAMS IN AN UPRIGHT POSITION. WHEN PLACING OR STORING BEAMS, ENSURE BEAM SUPPORTS ARE LOCATED ONLY UNDER THE SOLE PLATES.
 LOCATE HOLES FOR DIAPHRAGMS OR CROSS FRAMES AS SHOWN ON "FLORIDA I-BEAM DETAILS" SHEET. FORM HOLES WITH 2" INSIDE Ø PIPE AND PREVENT MOVEMENT DURING CASTING BY SECURELY FASTENING THE PIPE.
 CONTRACTOR IS RESPONSIBLE FOR INVESTIGATING THE CAPACITY OF BEAM FLANGES TO ENSURE FLANGES ARE ADEQUATE TO SUPPORT ALL CONSTRUCTION LOADS. A MINIMUM OF #4 REINFORCING BARS PLACED TRANSVERSELY AT 24" SPACING IS REQUIRED IN ALL FLORIDA I-BEAM TOP FLANGES.
 DEBONDING:
 1) FOR ALL DEBONDING MATERIAL, USE TUBULAR CONDUIT CAPABLE OF RESISTING THE PRESSURE EXERTED BY THE CONCRETE. WHEN USING SLIT CONDUIT, USE TWO CONDUITS WITH THE SLITS LOCATED ON OPPOSITE SIDES OF THE STRAND. USE CONDUIT MADE OF HIGH DENSITY POLYETHYLENE OR POLYPROPYLENE WITH A MINIMUM THICKNESS OF 0.025". USE CONDUIT WITH AN INSIDE DIAMETER THAT WILL PERMIT FREE MOVEMENT OF THE ENCASED STRAND, BUT NO LARGER THAN THE DIAMETER OF THE STRAND PLUS 1/8". PLACE CONDUIT ON THE STRAND AT THE LOCATION(S) SHOWN ON THE PLANS (±1") TO PREVENT BONDING OF THE CONCRETE. SECURE CONDUIT TO PREVENT ANY LONGITUDINAL MOVEMENT ALONG THE STRAND. PREVENT CONCRETE FROM ENTERING THE CONDUIT BY SEALING WITH TAPE. USE TAPE MANUFACTURED FROM A NON-CORROSIVE MATERIAL THAT IS COMPATIBLE WITH THE CONCRETE, CONDUIT, AND STEEL.
 2) RELEASE STRANDS IN ACCORDANCE WITH SECTION 704 OF THE STANDARD SPECIFICATIONS.
 3) WITHIN 48 HOURS OF DETENSIONING, SEAL THE OPENINGS BETWEEN THE STRANDS AND THE SHEATHING. USE AN APPROVED SEALANT THAT IS MADE OF EITHER EPOXY OR SILICONE. IF SILICONE SEALANT IS PROVIDED, USE A LOW MODULUS SILICONE SEALANT THAT IS WHITE IN COLOR.

③ NUMBER OF STRANDS SHOWN FOR ILLUSTRATION ONLY.

FIELD BEND STRANDS AS NECESSARY FOR OUTSIDE OF EXTERIOR BEAM ONLY.

③ NUMBER OF STRANDS SHOWN FOR ILLUSTRATION ONLY.

③ NUMBER OF STRANDS SHOWN FOR ILLUSTRATION ONLY.

③ NUMBER OF STRANDS SHOWN FOR ILLUSTRATION ONLY.

③ NUMBER OF STRANDS SHOWN FOR ILLUSTRATION ONLY.

③ NUMBER OF STRANDS SHOWN FOR ILLUSTRATION ONLY.

③ NUMBER OF STRANDS SHOWN FOR ILLUSTRATION ONLY.

③ NUMBER OF STRANDS SHOWN FOR ILLUSTRATION ONLY.

③ NUMBER OF STRANDS SHOWN FOR ILLUSTRATION ONLY.

③ NUMBER OF STRANDS SHOWN FOR ILLUSTRATION ONLY.

③ NUMBER OF STRANDS SHOWN FOR ILLUSTRATION ONLY.

③ NUMBER OF STRANDS SHOWN FOR ILLUSTRATION ONLY.

③ NUMBER OF STRANDS SHOWN FOR ILLUSTRATION ONLY.

③ NUMBER OF STRANDS SHOWN FOR ILLUSTRATION ONLY.

③ NUMBER OF STRANDS SHOWN FOR ILLUSTRATION ONLY.

③ NUMBER OF STRANDS SHOWN FOR ILLUSTRATION ONLY.

CONSULTANT NAME/LOGO	
SOUTH CAROLINA DEPARTMENT OF TRANSPORTATION	
FLORIDA I-BEAM GENERAL DETAILS	
COUNTY: ###	ROUTE: ###