


ELEVATION


AASHTO TYPE IV SHOWN, OTHERS SIMILAR.




18" CHANNEL

10" OR 12" CHANNEL

CHANNEL END DETAIL



SECTION A-A



WEB PLATE DETAIL






PLATE WASHER DETAIL


USE $3\frac{1}{2}$ " PLATE WASHER OVER ALL $1\frac{5}{16}$ "x $2\frac{3}{16}$ " HOLES
 USE 4 " PLATE WASHER OVER ALL $1\frac{1}{8}$ "x $2\frac{1}{2}$ " HOLES




DIAPHRAGM FACE FOR 18" CHANNEL



DIAPHRAGM FACE FOR 10" OR 12" CHANNEL



WEB FACE



CORNER CLIP

CHANNEL CONNECTION ANGLE DETAILS

NOTES:

PROVIDE STRUCTURAL STEEL SECTIONS, PLATES, AND PLATE WASHERS THAT CONFORM TO THE REQUIREMENTS OF AASHTO M 270, GRADE 50. GALVANIZE ALL COMPONENTS OF DIAPHRAGMS INCLUDING CONNECTION ANGLE OR CONNECTION PLATE AND PLATE WASHERS IN ACCORDANCE WITH AASHTO M 111. PERFORM GALVANIZING AFTER FABRICATION IS COMPLETED. ROUGHEN FAYING SURFACES OF BOLTED CONNECTIONS BY MEANS OF HAND-WIRE BRUSHING. POWER-WIRE BRUSHING IS NOT PERMITTED.

MAKE ALL BOLTED DIAPHRAGM CONNECTIONS WITH $\frac{7}{8}$ " OR 1 " ASTM F3125, GRADE A325 (TYPE 1) BOLTS. MECHANICALLY GALVANIZE BOLTS, HEAVY HEX NUTS, HARDENED WASHERS, AND DIRECT TENSION INDICATORS (DTI'S) IN ACCORDANCE WITH ASTM B 695 CLASS 50. FOR THE 1 " BOLT ASSEMBLIES, GALVANIZING IN ACCORDANCE WITH AASHTO M 232 MAY BE SUBSTITUTED FOR MECHANICAL GALVANIZING.

SUBMIT SHOP PLANS FOR STEEL INTERMEDIATE DIAPHRAGMS IN ACCORDANCE WITH THE STANDARD SPECIFICATIONS.

AFTER INSTALLATION OF STEEL DIAPHRAGMS, REPAIR ALL DAMAGED AREAS OF THE GALVANIZED FINISH IN ACCORDANCE WITH ASTM A 780. USE PAINT METHOD TO REPAIR FINISH ON HARDWARE.

FORM BOLT HOLES IN PRESTRESSED CONCRETE BEAMS USING 2 " INSIDE DIAMETER PIPE AND LEAVE PIPE IN PLACE AFTER FORMS ARE REMOVED.

TENSION BOLTS THROUGH THE BEAM WEB TO BE SNUG TIGHT AND THEN TURN THE BOLTS AN ADDITIONAL $\frac{1}{4}$ TURN. PEEN THREADS ON ALL BOLTS INSTALLED THROUGH THE BEAM WEB. INSTALL ALL OTHER BOLTS USING A DTI AND HARDENED WASHER WITH EACH BOLT ASSEMBLY TO VERIFY PROPER TENSIONING.

DO NOT PLACE DECK SLAB UNTIL ALL INTERMEDIATE DIAPHRAGMS ARE PROPERLY INSTALLED AND TIGHTENED IN EACH SPAN WHERE DECK CONCRETE WILL BE PLACED DURING THE POUR.

LEAVE STEEL INTERMEDIATE DIAPHRAGMS IN PLACE AS A PERMANENT PART OF THE COMPLETED STRUCTURE.

INCLUDE ALL COST OF FURNISHING AND INSTALLING STEEL INTERMEDIATE DIAPHRAGM ASSEMBLIES IN THE UNIT PRICE BID FOR PRESTRESSED CONCRETE BEAMS.

		CONNECTION DIMENSIONS			
BEAM	DIAPHRAGM	A	B	C	D
TYPE I MOD.	MC10X22	10"	4"	3"	5"
TYPE II	MC12X31	1'-0"	4"	4"	7"
TYPE III	MC18X42.7	1'-6"	5"	4"	1'-1"
TYPE IV	MC18X42.7	1'-6"	5"	4"	1'-1"

CONSULTANT NAME/LOGO

SOUTH CAROLINA
 DEPARTMENT OF TRANSPORTATION
**AASHTO I-BEAM STEEL
 INTERMEDIATE DIAPHRAGM
 DETAILS - ALT 1**

COUNTY: ####

ROUTE: ####

DRAWING NUMBER: 704-AASHTO.STLINTDIA.CHAN.SK000

THIS DRAWING IS FURNISHED FOR INFORMATION ONLY. ALL DIMENSIONS SHOWN ARE SHEET SPECIFIC. ANY USE OF THIS DESIGN AND DRAWING, INCLUDING DIMENSIONS, MUST BE CHECKED BY THE USER'S ENGINEER TO ENSURE DESIGN IS ADEQUATE FOR THE INTENDED USE. ALL DRAWINGS MUST BE SIGNED AND SEALED BY A SOUTH CAROLINA REGISTERED PROFESSIONAL ENGINEER WHEN USED.

Dylan.Danks 6/21/2024 3:30:47 PM 704_StlIntDia.dgn

REV.	BY	CHK.	DATE	DESCRIPTION OF REVISION

REVIEWED	QUAN.	DR.	DES.	BY	CHK.	DATE
		DMD	AEL			04-24

NOTES:

PROVIDE STRUCTURAL STEEL SECTIONS, PLATES, AND PLATE WASHERS THAT CONFORM TO THE REQUIREMENTS OF AASHTO M 270, GRADE 50. GALVANIZE ALL COMPONENTS OF DIAPHRAGMS INCLUDING CONNECTION ANGLE OR CONNECTION PLATE AND PLATE WASHERS IN ACCORDANCE WITH AASHTO M 111. PERFORM GALVANIZING AFTER FABRICATION IS COMPLETED. ROUGHEN FAYING SURFACES OF BOLTED CONNECTIONS BY MEANS OF HAND-WIRE BRUSHING. POWER-WIRE BRUSHING IS NOT PERMITTED.

MAKE ALL BOLTED DIAPHRAGM CONNECTIONS WITH 7/8" OR 1" ASTM F3125, GRADE A325 (TYPE 1) BOLTS. MECHANICALLY GALVANIZE BOLTS, HEAVY HEX NUTS, HARDENED WASHERS, AND DIRECT TENSION INDICATORS (DTI'S) IN ACCORDANCE WITH ASTM B 695 CLASS 50. FOR THE 1" BOLT ASSEMBLIES, GALVANIZING IN ACCORDANCE WITH AASHTO M 232 MAY BE SUBSTITUTED FOR MECHANICAL GALVANIZING.

SUBMIT SHOP PLANS FOR STEEL INTERMEDIATE DIAPHRAGMS IN ACCORDANCE WITH THE STANDARD SPECIFICATIONS.

AFTER INSTALLATION OF STEEL DIAPHRAGMS, REPAIR ALL DAMAGED AREAS OF THE GALVANIZED FINISH IN ACCORDANCE WITH ASTM A 780. USE PAINT METHOD TO REPAIR FINISH ON HARDWARE.


FORM BOLT HOLES IN PRESTRESSED CONCRETE BEAMS USING 2" INSIDE DIAMETER PIPE AND LEAVE PIPE IN PLACE AFTER FORMS ARE REMOVED.

TENSION BOLTS THROUGH THE BEAM WEB TO BE SNUG TIGHT AND THEN TURN THE BOLTS AN ADDITIONAL 1/4 TURN. PEEN THREADS ON ALL BOLTS INSTALLED THROUGH THE BEAM WEB. INSTALL ALL OTHER BOLTS USING A DTI AND HARDENED WASHER WITH EACH BOLT ASSEMBLY TO VERIFY PROPER TENSIONING.

DO NOT PLACE DECK SLAB UNTIL ALL INTERMEDIATE DIAPHRAGMS ARE PROPERLY INSTALLED AND TIGHTENED IN EACH SPAN WHERE DECK CONCRETE WILL BE PLACED DURING THE POUR.


LEAVE STEEL INTERMEDIATE DIAPHRAGMS IN PLACE AS A PERMANENT PART OF THE COMPLETED STRUCTURE.

INCLUDE ALL COST OF FURNISHING AND INSTALLING STEEL INTERMEDIATE DIAPHRAGM ASSEMBLIES IN THE UNIT PRICE BID FOR PRESTRESSED CONCRETE BEAMS.




ELEVATION

AASHTO TYPE IV SHOWN, OTHERS SIMILAR.




18" CHANNEL




10" OR 12" CHANNEL

CHANNEL END DETAIL



SECTION A-A

LEFT SKEW SHOWN. RIGHT SKEW SIMILAR BY MIRROR ABOUT A LINE PARALLEL TO H.S. BOLT CENTERLINES.



WEB PLATE DETAIL





PLATE WASHER DETAIL


USE 3 1/2" PLATE WASHER OVER ALL 1 5/16"x2 3/16" HOLES
USE 4" PLATE WASHER OVER ALL 1 1/8"x2 1/2" HOLES




DIAPHRAGM FACE FOR 18" CHANNEL

DIAPHRAGM FACE FOR 10" OR 12" CHANNEL

WEB FACE



CORNER CLIP



SECTION B-B

		CONNECTION DIMENSIONS			
BEAM	DIAPHRAGM	A	B	C	D
TYPE I MOD.	MC10X22	10"	4"	3"	5"
TYPE II	MC12X31	1'-0"	4"	4"	7"
TYPE III	MC18X42.7	1'-6"	5"	4"	1'-1"
TYPE IV	MC18X42.7	1'-6"	5"	4"	1'-1"

CONSULTANT NAME/LOGO

**SOUTH CAROLINA
DEPARTMENT OF TRANSPORTATION
AASHTO I-BEAM STEEL
INTERMEDIATE DIAPHRAGM
DETAILS - ALT 2**

COUNTY: ####

ROUTE: ####

DRAWING NUMBER: 704-AASHTO.STLINTDIA.CHAN.SKUNDER20

THIS DRAWING IS FURNISHED FOR INFORMATION ONLY. ALL DIMENSIONS SHOWN ARE SHEET SPECIFIC. ANY USE OF THIS DESIGN AND DRAWING, INCLUDING DIMENSIONS, MUST BE CHECKED BY THE USER'S ENGINEER TO ENSURE DESIGN IS ADEQUATE FOR THE INTENDED USE. ALL DRAWINGS MUST BE SIGNED AND SEALED BY A SOUTH CAROLINA REGISTERED PROFESSIONAL ENGINEER WHEN USED.

REV.	DATE	BY	CHK.	DESCRIPTION OF REVISION

REVIEWED	DATE	BY	CHK.
QUAN.			
DR.	04-24		
DES.			

Dylan.Danks 6/21/2024 3:30:49 PM 704_StlIntDia.dgn

NOTES:

PROVIDE STRUCTURAL STEEL SECTIONS, PLATES, AND PLATE WASHERS THAT CONFORM TO THE REQUIREMENTS OF AASHTO M 270, GRADE 50. GALVANIZE ALL COMPONENTS OF DIAPHRAGMS INCLUDING CONNECTION ANGLE OR CONNECTION PLATE AND PLATE WASHERS IN ACCORDANCE WITH AASHTO M 111. PERFORM GALVANIZING AFTER FABRICATION IS COMPLETED. ROUGHEN FAYING SURFACES OF BOLTED CONNECTIONS BY MEANS OF HAND-WIRE BRUSHING. POWER-WIRE BRUSHING IS NOT PERMITTED.

MAKE ALL BOLTED DIAPHRAGM CONNECTIONS WITH 7/8" OR 1" ASTM F3125, GRADE A325 (TYPE 1) BOLTS. MECHANICALLY GALVANIZE BOLTS, HEAVY HEX NUTS, HARDENED WASHERS, AND DIRECT TENSION INDICATORS (DTI'S) IN ACCORDANCE WITH ASTM B 695 CLASS 50. FOR THE 1" BOLT ASSEMBLIES, GALVANIZING IN ACCORDANCE WITH AASHTO M 232 MAY BE SUBSTITUTED FOR MECHANICAL GALVANIZING.

SUBMIT SHOP PLANS FOR STEEL INTERMEDIATE DIAPHRAGMS IN ACCORDANCE WITH THE STANDARD SPECIFICATIONS.

AFTER INSTALLATION OF STEEL DIAPHRAGMS, REPAIR ALL DAMAGED AREAS OF THE GALVANIZED FINISH IN ACCORDANCE WITH ASTM A 780. USE PAINT METHOD TO REPAIR FINISH ON HARDWARE.


FORM BOLT HOLES IN PRESTRESSED CONCRETE BEAMS USING 2" INSIDE DIAMETER PIPE AND LEAVE PIPE IN PLACE AFTER FORMS ARE REMOVED.

TENSION BOLTS THROUGH THE BEAM WEB TO BE SNUG TIGHT AND THEN TURN THE BOLTS AN ADDITIONAL 1/4 TURN. PEEN THREADS ON ALL BOLTS INSTALLED THROUGH THE BEAM WEB. INSTALL ALL OTHER BOLTS USING A DTI AND HARDENED WASHER WITH EACH BOLT ASSEMBLY TO VERIFY PROPER TENSIONING.


DO NOT PLACE DECK SLAB UNTIL ALL INTERMEDIATE DIAPHRAGMS ARE PROPERLY INSTALLED AND TIGHTENED IN EACH SPAN WHERE DECK CONCRETE WILL BE PLACED DURING THE POUR.

LEAVE STEEL INTERMEDIATE DIAPHRAGMS IN PLACE AS A PERMANENT PART OF THE COMPLETED STRUCTURE.


INCLUDE ALL COST OF FURNISHING AND INSTALLING STEEL INTERMEDIATE DIAPHRAGM ASSEMBLIES IN THE UNIT PRICE BID FOR PRESTRESSED CONCRETE BEAMS.




ELEVATION



CHANNEL END DETAIL



SECTION A-A



WEB PLATE DETAIL






PLATE WASHER DETAIL

USE 3 1/2" PLATE WASHER OVER ALL 1 5/16"x2 3/16" HOLES
USE 4" PLATE WASHER OVER ALL 1 1/8"x2 1/2" HOLES



DIAPHRAGM FACE

WEB FACE



CORNER CLIP

CHANNEL CONNECTION ANGLE DETAILS

CONNECTION DIMENSIONS				
BEAM	DIAPHRAGM	A	B	D
54" MOD. B.T.	MC18X42.7	1'-6"	5"	4"

CONSULTANT NAME/LOGO

SOUTH CAROLINA
DEPARTMENT OF TRANSPORTATION
MODIFIED BULB TEE BEAM
STEEL INTERMEDIATE
DIAPHRAGM DETAILS - ALT 1

THIS DRAWING IS FURNISHED FOR INFORMATION ONLY. ALL DIMENSIONS SHOWN ARE SHEET SPECIFIC. ANY USE OF THIS DESIGN AND DRAWING, INCLUDING DIMENSIONS, MUST BE CHECKED BY THE USER'S ENGINEER TO ENSURE DESIGN IS ADEQUATE FOR THE INTENDED USE. ALL DRAWINGS MUST BE SIGNED AND SEALED BY A SOUTH CAROLINA REGISTERED PROFESSIONAL ENGINEER WHEN USED.

COUNTY: ###

ROUTE: ###

DRAWING NUMBER: 704-MBT.STLINTDIA.CHAN.SK000

REV.	BY	CHK.	DATE	DESCRIPTION OF REVISION

REVIEWED	QUAN.	DR.	DES.	BY	CHK.	DATE

Dylan.Danks 6/21/2024 3:30:51 PM 704_StlIntDia.dgn

NOTES:

PROVIDE STRUCTURAL STEEL SECTIONS, PLATES, AND PLATE WASHERS THAT CONFORM TO THE REQUIREMENTS OF AASHTO M 270, GRADE 50. GALVANIZE ALL COMPONENTS OF DIAPHRAGMS INCLUDING CONNECTION ANGLE OR CONNECTION PLATE AND PLATE WASHERS IN ACCORDANCE WITH AASHTO M 111. PERFORM GALVANIZING AFTER FABRICATION IS COMPLETED. ROUGHEN FAYING SURFACES OF BOLTED CONNECTIONS BY MEANS OF HAND-WIRE BRUSHING. POWER-WIRE BRUSHING IS NOT PERMITTED.

MAKE ALL BOLTED DIAPHRAGM CONNECTIONS WITH 7/8" OR 1" ASTM F3125, GRADE A325 (TYPE 1) BOLTS. MECHANICALLY GALVANIZE BOLTS, HEAVY HEX NUTS, HARDENED WASHERS, AND DIRECT TENSION INDICATORS (DTI'S) IN ACCORDANCE WITH ASTM B 695 CLASS 50. FOR THE 1" BOLT ASSEMBLIES, GALVANIZING IN ACCORDANCE WITH AASHTO M 232 MAY BE SUBSTITUTED FOR MECHANICAL GALVANIZING.

SUBMIT SHOP PLANS FOR STEEL INTERMEDIATE DIAPHRAGMS IN ACCORDANCE WITH THE STANDARD SPECIFICATIONS.

AFTER INSTALLATION OF STEEL DIAPHRAGMS, REPAIR ALL DAMAGED AREAS OF THE GALVANIZED FINISH IN ACCORDANCE WITH ASTM A 780. USE PAINT METHOD TO REPAIR FINISH ON HARDWARE.


FORM BOLT HOLES IN PRESTRESSED CONCRETE BEAMS USING 2" INSIDE DIAMETER PIPE AND LEAVE PIPE IN PLACE AFTER FORMS ARE REMOVED.

TENSION BOLTS THROUGH THE BEAM WEB TO BE SNUG TIGHT AND THEN TURN THE BOLTS AN ADDITIONAL 1/4 TURN. PEEN THREADS ON ALL BOLTS INSTALLED THROUGH THE BEAM WEB. INSTALL ALL OTHER BOLTS USING A DTI AND HARDENED WASHER WITH EACH BOLT ASSEMBLY TO VERIFY PROPER TENSIONING.


DO NOT PLACE DECK SLAB UNTIL ALL INTERMEDIATE DIAPHRAGMS ARE PROPERLY INSTALLED AND TIGHTENED IN EACH SPAN WHERE DECK CONCRETE WILL BE PLACED DURING THE POUR.

LEAVE STEEL INTERMEDIATE DIAPHRAGMS IN PLACE AS A PERMANENT PART OF THE COMPLETED STRUCTURE.


INCLUDE ALL COST OF FURNISHING AND INSTALLING STEEL INTERMEDIATE DIAPHRAGM ASSEMBLIES IN THE UNIT PRICE BID FOR PRESTRESSED CONCRETE BEAMS.



ELEVATION




CHANNEL END DETAIL



SECTION A-A

LEFT SKEW SHOWN. RIGHT SKEW SIMILAR BY MIRROR ABOUT A LINE PARALLEL TO H.S. BOLT CENTERLINES.



WEB PLATE DETAIL






PLATE WASHER DETAIL

USE 3 1/2" PLATE WASHER OVER ALL 1 5/16"x2 3/16" HOLES
USE 4" PLATE WASHER OVER ALL 1 1/8"x2 1/2" HOLES




DIAPHRAGM FACE

WEB FACE



CORNER CLIP

CHANNEL CONNECTION BENT PLATE DETAILS



SECTION B-B

CONNECTION DIMENSIONS					
BEAM	DIAPHRAGM	A	B	C	D
54" MOD. B.T.	MC18X42.7	1'-6"	5"	4"	1'-1"


REV.	BY	CHK.	DATE	DESCRIPTION OF REVISION

REVIEWED	BY	CHK.	DATE
QUAN.	DMD	AEL	04-24
DES.			


THIS DRAWING IS FURNISHED FOR INFORMATION ONLY. ALL DIMENSIONS SHOWN ARE SHEET SPECIFIC. ANY USE OF THIS DESIGN AND DRAWING, INCLUDING DIMENSIONS, MUST BE CHECKED BY THE USER'S ENGINEER TO ENSURE DESIGN IS ADEQUATE FOR THE INTENDED USE. ALL DRAWINGS MUST BE SIGNED AND SEALED BY A SOUTH CAROLINA REGISTERED PROFESSIONAL ENGINEER WHEN USED.

CONSULTANT NAME/LOGO	
SOUTH CAROLINA DEPARTMENT OF TRANSPORTATION	
MODIFIED BULB TEE BEAM STEEL INTERMEDIATE DIAPHRAGM DETAILS - ALT 2	
COUNTY: ####	ROUTE: ####


Dylan.Danks 6/21/2024 3:30:51 PM 704_StlIntDia.dgn



ELEVATION




CHANNEL END DETAIL



SECTION A-A

LEFT SKEW SHOWN. RIGHT SKEW SIMILAR BY MIRROR ABOUT A LINE PARALLEL TO H.S. BOLT CENTERLINES.



WEB PLATE DETAIL






PLATE WASHER DETAIL

USE 3 1/2" PLATE WASHER OVER ALL 15/16"x2 3/16" HOLES
USE 4" PLATE WASHER OVER ALL 1 1/8"x2 1/2" HOLES



DIAPHRAGM FACE

WEB FACE



CORNER CLIP

CHANNEL CONNECTION ANGLE DETAILS

NOTES:

PROVIDE STRUCTURAL STEEL SECTIONS, PLATES, AND PLATE WASHERS THAT CONFORM TO THE REQUIREMENTS OF AASHTO M 270, GRADE 50. GALVANIZE ALL COMPONENTS OF DIAPHRAGMS INCLUDING CONNECTION ANGLE OR CONNECTION PLATE AND PLATE WASHERS IN ACCORDANCE WITH AASHTO M 111. PERFORM GALVANIZING AFTER FABRICATION IS COMPLETED. ROUGHEN FAYING SURFACES OF BOLTED CONNECTIONS BY MEANS OF HAND-WIRE BRUSHING. POWER-WIRE BRUSHING IS NOT PERMITTED.

MAKE ALL BOLTED DIAPHRAGM CONNECTIONS WITH 7/8" OR 1" ASTM F3125, GRADE A325 (TYPE 1) BOLTS. MECHANICALLY GALVANIZE BOLTS, HEAVY HEX NUTS, HARDENED WASHERS, AND DIRECT TENSION INDICATORS (DTI'S) IN ACCORDANCE WITH ASTM B 695 CLASS 50. FOR THE 1" BOLT ASSEMBLIES, GALVANIZING IN ACCORDANCE WITH AASHTO M 232 MAY BE SUBSTITUTED FOR MECHANICAL GALVANIZING.

SUBMIT SHOP PLANS FOR STEEL INTERMEDIATE DIAPHRAGMS IN ACCORDANCE WITH THE STANDARD SPECIFICATIONS.

AFTER INSTALLATION OF STEEL DIAPHRAGMS, REPAIR ALL DAMAGED AREAS OF THE GALVANIZED FINISH IN ACCORDANCE WITH ASTM A 780. USE PAINT METHOD TO REPAIR FINISH ON HARDWARE.

FORM BOLT HOLES IN PRESTRESSED CONCRETE BEAMS USING 2" INSIDE DIAMETER PIPE AND LEAVE PIPE IN PLACE AFTER FORMS ARE REMOVED.

TENSION BOLTS THROUGH THE BEAM WEB TO BE SNUG TIGHT AND THEN TURN THE BOLTS AN ADDITIONAL 1/4 TURN. PEEN THREADS ON ALL BOLTS INSTALLED THROUGH THE BEAM WEB. INSTALL ALL OTHER BOLTS USING A DTI AND HARDENED WASHER WITH EACH BOLT ASSEMBLY TO VERIFY PROPER TENSIONING.

DO NOT PLACE DECK SLAB UNTIL ALL INTERMEDIATE DIAPHRAGMS ARE PROPERLY INSTALLED AND TIGHTENED IN EACH SPAN WHERE DECK CONCRETE WILL BE PLACED DURING THE POUR.

LEAVE STEEL INTERMEDIATE DIAPHRAGMS IN PLACE AS A PERMANENT PART OF THE COMPLETED STRUCTURE.

INCLUDE ALL COST OF FURNISHING AND INSTALLING STEEL INTERMEDIATE DIAPHRAGM ASSEMBLIES IN THE UNIT PRICE BID FOR PRESTRESSED CONCRETE BEAMS.

CONNECTION DIMENSIONS				
BEAM	DIAPHRAGM	A	B	D
54" MOD. B.T.	MC18X42.7	1'-6"	5"	4"

REV.	BY	CHK.	DATE	DESCRIPTION OF REVISION

REVIEWED	BY	CHK.	DATE
QUAN.	DMD	AEL	04-24
DES.			

THIS DRAWING IS FURNISHED FOR INFORMATION ONLY. ALL DIMENSIONS SHOWN ARE SHEET SPECIFIC. ANY USE OF THIS DESIGN AND DRAWING, INCLUDING DIMENSIONS, MUST BE CHECKED BY THE USER'S ENGINEER TO ENSURE DESIGN IS ADEQUATE FOR THE INTENDED USE. ALL DRAWINGS MUST BE SIGNED AND SEALED BY A SOUTH CAROLINA REGISTERED PROFESSIONAL ENGINEER WHEN USED.


CONSULTANT NAME/LOGO

SOUTH CAROLINA DEPARTMENT OF TRANSPORTATION

MODIFIED BULB TEE BEAM STEEL INTERMEDIATE DIAPHRAGM DETAILS - ALT 3


COUNTY: #### ROUTE: ####

Dylan.Danks 6/21/2024 3:30:52 PM 704_StlIntDia.dgn



ELEVATION

72" MODIFIED BULB TEE SHOWN, OTHERS SIMILAR.




WEB PLATE DETAIL

WEB FACE

DIAPHRAGM FACE - PL 1

DIAPHRAGM FACE - PL 2

CROSS FRAME CONNECTION BENT PLATE DETAILS



SECTION A-A






PLATE WASHER DETAIL

USE 3 1/2" PLATE WASHER OVER ALL 1 3/16" x 2 3/16" HOLES
USE 4" PLATE WASHER OVER ALL 1 1/8" x 2 1/2" HOLES




CROSS FRAME DETAILS

NOTE: BOLTS, NUTS, AND WASHERS NOT SHOWN FOR CLARITY.



CORNER CLIP DETAIL



SECTION B-B

NOTES:

PROVIDE STRUCTURAL STEEL SECTIONS, PLATES, AND PLATE WASHERS THAT CONFORM TO THE REQUIREMENTS OF AASHTO M 270, GRADE 50. GALVANIZE ALL COMPONENTS OF CROSS FRAMES INCLUDING CONNECTION PLATE AND PLATE WASHERS IN ACCORDANCE WITH AASHTO M 111. PERFORM GALVANIZING AFTER FABRICATION IS COMPLETED. ROUGHEN FAYING SURFACES OF BOLTED CONNECTIONS BY MEANS OF HAND-WIRE BRUSHING. POWER-WIRE BRUSHING IS NOT PERMITTED.

MAKE ALL BOLTED CROSS FRAME CONNECTIONS WITH 7/8" OR 1" ASTM F3125, GRADE A325 (TYPE 1) BOLTS, MECHANICALLY GALVANIZE BOLTS, HEAVY HEX NUTS, HARDENED WASHERS, AND DIRECT TENSION INDICATORS (DTI'S) IN ACCORDANCE WITH ASTM B 695 CLASS 50. FOR THE 1" BOLT ASSEMBLIES, GALVANIZING IN ACCORDANCE WITH AASHTO M 232 MAY BE SUBSTITUTED FOR MECHANICAL GALVANIZING.

SUBMIT SHOP PLANS FOR STEEL CROSS FRAMES IN ACCORDANCE WITH THE STANDARD SPECIFICATIONS.

AFTER INSTALLATION OF STEEL CROSS FRAMES, REPAIR ALL DAMAGED AREAS OF THE GALVANIZED FINISH IN ACCORDANCE WITH ASTM A 780. USE PAINT METHOD TO REPAIR FINISH ON HARDWARE.

FORM BOLT HOLES IN PRESTRESSED CONCRETE BEAMS USING 2" INSIDE DIAMETER PIPE AND LEAVE PIPE IN PLACE AFTER FORMS ARE REMOVED.

TENSION BOLTS THROUGH THE BEAM WEB TO BE SNUG TIGHT AND THEN TURN THE BOLTS AN ADDITIONAL 1/4 TURN. PEEN THREADS ON ALL BOLTS INSTALLED THROUGH THE BEAM WEB. INSTALL ALL OTHER BOLTS USING A DTI AND HARDENED WASHER WITH EACH BOLT ASSEMBLY TO VERIFY PROPER TENSIONING.

DO NOT PLACE DECK SLAB UNTIL ALL CROSS FRAMES ARE PROPERLY INSTALLED AND TIGHTENED IN EACH SPAN WHERE DECK CONCRETE WILL BE PLACED DURING THE POUR.

LEAVE STEEL CROSS FRAMES IN PLACE AS A PERMANENT PART OF THE COMPLETED STRUCTURE.

BEAM	CONNECTION DIMENSIONS	
	A	B
63" MOD. B.T.	3'-4"	11"
72" MOD. B.T.	4'-1"	1'-2"
74" MOD. B.T.	4'-1"	1'-2"
78" MOD. B.T.	4'-7"	1'-4"

CONSULTANT NAME/LOGO

SOUTH CAROLINA
DEPARTMENT OF TRANSPORTATION
**MODIFIED BULB TEE BEAM
STEEL INTERMEDIATE CROSS
FRAME DETAILS - ALT 1**

COUNTY: ####

ROUTE: ####


DRAWING NUMBER: 704-MBT.STLINTDIA.CROSS.SK000

REV.	BY	CHK.	DATE	DESCRIPTION OF REVISION

REVIEWED	BY	CHK.	DATE
QUAN.	DMD	AEL	04-24
DR.			
DES.			


Dylan.Danks 6/21/2024 3:30:53 PM 704_StlIntDia.dgn

THIS DRAWING IS FURNISHED FOR INFORMATION ONLY. ALL DIMENSIONS SHOWN ARE SHEET SPECIFIC. ANY USE OF THIS DESIGN AND DRAWING, INCLUDING DIMENSIONS, MUST BE CHECKED BY THE USER'S ENGINEER TO ENSURE DESIGN IS ADEQUATE FOR THE INTENDED USE. ALL DRAWINGS MUST BE SIGNED AND SEALED BY A SOUTH CAROLINA REGISTERED PROFESSIONAL ENGINEER WHEN USED.



ELEVATION

72" MODIFIED BULB TEE SHOWN, OTHERS SIMILAR.




WEB FACE

DIAPHRAGM FACE - PL 1

DIAPHRAGM FACE - PL 2

WEB PLATE DETAIL

CROSS FRAME CONNECTION BENT PLATE DETAILS



SECTION A-A

LEFT SKEW SHOWN. RIGHT SKEW SIMILAR BY MIRROR ABOUT A LINE PARALLEL TO H.S. BOLT CENTERLINES.






PLATE WASHER DETAIL

USE 3 1/2" PLATE WASHER OVER ALL 1 5/16" x 2 3/16" HOLES
USE 4" PLATE WASHER OVER ALL 1 3/8" x 2 1/2" HOLES




CROSS FRAME DETAILS

NOTE: BOLTS, NUTS, AND WASHERS NOT SHOWN FOR CLARITY.



CORNER CLIP DETAIL



SECTION B-B

NOTES:

PROVIDE STRUCTURAL STEEL SECTIONS, PLATES, AND PLATE WASHERS THAT CONFORM TO THE REQUIREMENTS OF AASHTO M 270, GRADE 50. GALVANIZE ALL COMPONENTS OF CROSS FRAMES INCLUDING CONNECTION PLATE AND PLATE WASHERS IN ACCORDANCE WITH AASHTO M 111. PERFORM GALVANIZING AFTER FABRICATION IS COMPLETED. ROUGHEN FAYING SURFACES OF BOLTED CONNECTIONS BY MEANS OF HAND-WIRE BRUSHING. POWER-WIRE BRUSHING IS NOT PERMITTED.

MAKE ALL BOLTED CROSS FRAME CONNECTIONS WITH 7/8" OR 1" ASTM F3125, GRADE A325 (TYPE 1) BOLTS. MECHANICALLY GALVANIZE BOLTS, HEAVY HEX NUTS, HARDENED WASHERS, AND DIRECT TENSION INDICATORS (DTI'S) IN ACCORDANCE WITH ASTM B 695 CLASS 50. FOR THE 1" BOLT ASSEMBLIES, GALVANIZING IN ACCORDANCE WITH AASHTO M 232 MAY BE SUBSTITUTED FOR MECHANICAL GALVANIZING.

SUBMIT SHOP PLANS FOR STEEL CROSS FRAMES IN ACCORDANCE WITH THE STANDARD SPECIFICATIONS.

AFTER INSTALLATION OF STEEL CROSS FRAMES, REPAIR ALL DAMAGED AREAS OF THE GALVANIZED FINISH IN ACCORDANCE WITH ASTM A 780. USE PAINT METHOD TO REPAIR FINISH ON HARDWARE.

FORM BOLT HOLES IN PRESTRESSED CONCRETE BEAMS USING 2" INSIDE DIAMETER PIPE AND LEAVE PIPE IN PLACE AFTER FORMS ARE REMOVED.

TENSION BOLTS THROUGH THE BEAM WEB TO BE SNUG TIGHT AND THEN TURN THE BOLTS AN ADDITIONAL 1/4 TURN. PEEN THREADS ON ALL BOLTS INSTALLED THROUGH THE BEAM WEB. INSTALL ALL OTHER BOLTS USING A DTI AND HARDENED WASHER WITH EACH BOLT ASSEMBLY TO VERIFY PROPER TENSIONING.

DO NOT PLACE DECK SLAB UNTIL ALL CROSS FRAMES ARE PROPERLY INSTALLED AND TIGHTENED IN EACH SPAN WHERE DECK CONCRETE WILL BE PLACED DURING THE POUR.

LEAVE STEEL CROSS FRAMES IN PLACE AS A PERMANENT PART OF THE COMPLETED STRUCTURE.

BEAM	CONNECTION DIMENSIONS	
	A	B
63" MOD. B.T.	3'-4"	11"
72" MOD. B.T.	4'-1"	1'-2"
74" MOD. B.T.	4'-1"	1'-2"
78" MOD. B.T.	4'-7"	1'-4"

CONSULTANT NAME/LOGO

SOUTH CAROLINA
DEPARTMENT OF TRANSPORTATION
**MODIFIED BULB TEE BEAM
STEEL INTERMEDIATE CROSS
FRAME DETAILS - ALT 2**

COUNTY: ###

ROUTE: ###

THIS DRAWING IS FURNISHED FOR INFORMATION ONLY. ALL DIMENSIONS SHOWN ARE SHEET SPECIFIC. ANY USE OF THIS DESIGN AND DRAWING, INCLUDING DIMENSIONS, MUST BE CHECKED BY THE USER'S ENGINEER TO ENSURE DESIGN IS ADEQUATE FOR THE INTENDED USE. ALL DRAWINGS MUST BE SIGNED AND SEALED BY A SOUTH CAROLINA REGISTERED PROFESSIONAL ENGINEER WHEN USED.

REV.	BY	CHK.	DATE	DESCRIPTION OF REVISION

REVIEWED	QUAN.	DR.	DMD	AEL	04-24

Dylan.Danks 6/21/2024 3:30:54 PM 704_StlIntDia.dgn

NOTES:

PROVIDE STRUCTURAL STEEL SECTIONS, PLATES, AND PLATE WASHERS THAT CONFORM TO THE REQUIREMENTS OF AASHTO M 270, GRADE 50. GALVANIZE ALL COMPONENTS OF DIAPHRAGMS INCLUDING CONNECTION ANGLE OR CONNECTION PLATE AND PLATE WASHERS IN ACCORDANCE WITH AASHTO M 111. PERFORM GALVANIZING AFTER FABRICATION IS COMPLETED. ROUGHEN FAYING SURFACES OF BOLTED CONNECTIONS BY MEANS OF HAND-WIRE BRUSHING. POWER-WIRE BRUSHING IS NOT PERMITTED.

MAKE ALL BOLTED DIAPHRAGM CONNECTIONS WITH 7/8" OR 1" ASTM F3125, GRADE A325 (TYPE 1) BOLTS. MECHANICALLY GALVANIZE BOLTS, HEAVY HEX NUTS, HARDENED WASHERS, AND DIRECT TENSION INDICATORS (DTI'S) IN ACCORDANCE WITH ASTM B 695 CLASS 50. FOR THE 1" BOLT ASSEMBLIES, GALVANIZING IN ACCORDANCE WITH AASHTO M 232 MAY BE SUBSTITUTED FOR MECHANICAL GALVANIZING.

SUBMIT SHOP PLANS FOR STEEL INTERMEDIATE DIAPHRAGMS IN ACCORDANCE WITH THE STANDARD SPECIFICATIONS.

AFTER INSTALLATION OF STEEL DIAPHRAGMS, REPAIR ALL DAMAGED AREAS OF THE GALVANIZED FINISH IN ACCORDANCE WITH ASTM A 780. USE PAINT METHOD TO REPAIR FINISH ON HARDWARE.


FORM BOLT HOLES IN PRESTRESSED CONCRETE BEAMS USING 2" INSIDE DIAMETER PIPE AND LEAVE PIPE IN PLACE AFTER FORMS ARE REMOVED.

TENSION BOLTS THROUGH THE BEAM WEB TO BE SNUG TIGHT AND THEN TURN THE BOLTS AN ADDITIONAL 1/4 TURN. PEEN THREADS ON ALL BOLTS INSTALLED THROUGH THE BEAM WEB. INSTALL ALL OTHER BOLTS USING A DTI AND HARDENED WASHER WITH EACH BOLT ASSEMBLY TO VERIFY PROPER TENSIONING.

DO NOT PLACE DECK SLAB UNTIL ALL INTERMEDIATE DIAPHRAGMS ARE PROPERLY INSTALLED AND TIGHTENED IN EACH SPAN WHERE DECK CONCRETE WILL BE PLACED DURING THE POUR.


LEAVE STEEL INTERMEDIATE DIAPHRAGMS IN PLACE AS A PERMANENT PART OF THE COMPLETED STRUCTURE.

INCLUDE ALL COST OF FURNISHING AND INSTALLING STEEL INTERMEDIATE DIAPHRAGM ASSEMBLIES IN THE UNIT PRICE BID FOR PRESTRESSED CONCRETE BEAMS.




ELEVATION

54" FLORIDA I-BEAM SHOWN, OTHERS SIMILAR.




18" CHANNEL

10" CHANNEL




6" CHANNEL

CHANNEL END DETAIL



SECTION A-A



10" OR 18" CHANNEL

6" CHANNEL

WEB PLATE DETAIL




PLATE WASHER DETAIL

USE 3 1/2" PLATE WASHER OVER ALL 1 5/16" x 2 3/16" HOLES
USE 4" PLATE WASHER OVER ALL 1 1/8" x 2 1/2" HOLES


BEAM	DIAPHRAGM	CONNECTION DIMENSIONS			
		A	B	C	D
36" F.I.B.	MC6X18	3 1/2"	N/A	1 3/4"	N/A
45" F.I.B.	MC10X22	10"	4"	3"	5"
54" F.I.B.	MC18X42.7	1'-6"	5"	4"	1'-1"
63" F.I.B.	MC18X42.7	1'-6"	5"	4"	1'-1"
72" F.I.B.	MC18X42.7	1'-6"	5"	4"	1'-1"

CONSULTANT NAME/LOGO

SOUTH CAROLINA
DEPARTMENT OF TRANSPORTATION
**FLORIDA I-BEAM STEEL
INTERMEDIATE DIAPHRAGM
DETAILS - ALT 1**

COUNTY: ##### ROUTE: #####

DRAWING NUMBER: 704-FIB.STLINTDIA.CHAN.SK000



DIAPHRAGM FACE FOR 18" CHANNEL

DIAPHRAGM FACE FOR 10" CHANNEL

DIAPHRAGM FACE FOR 6" CHANNEL

WEB FACE FOR 10" OR 18" CHANNEL

WEB FACE FOR 6" CHANNEL

CORNER CLIP

CHANNEL CONNECTION ANGLE DETAILS

THIS DRAWING IS FURNISHED FOR INFORMATION ONLY. ALL DIMENSIONS SHOWN ARE SHEET SPECIFIC. ANY USE OF THIS DESIGN AND DRAWING, INCLUDING DIMENSIONS, MUST BE CHECKED BY THE USER'S ENGINEER TO ENSURE DESIGN IS ADEQUATE FOR THE INTENDED USE. ALL DRAWINGS MUST BE SIGNED AND SEALED BY A SOUTH CAROLINA REGISTERED PROFESSIONAL ENGINEER WHEN USED.

Dylan.Danks 6/21/2024 3:30:56 PM 704_StlIntDia.dgn

REV.	BY	CHK.	DATE	DESCRIPTION OF REVISION

REVIEWED	QUAN.	DR.	DES.	BY	CHK.	DATE

NOTES:

PROVIDE STRUCTURAL STEEL SECTIONS, PLATES, AND PLATE WASHERS THAT CONFORM TO THE REQUIREMENTS OF AASHTO M 270, GRADE 50. GALVANIZE ALL COMPONENTS OF DIAPHRAGMS INCLUDING CONNECTION ANGLE OR CONNECTION PLATE AND PLATE WASHERS IN ACCORDANCE WITH AASHTO M 111. PERFORM GALVANIZING AFTER FABRICATION IS COMPLETED. ROUGHEN FAYING SURFACES OF BOLTED CONNECTIONS BY MEANS OF HAND-WIRE BRUSHING. POWER-WIRE BRUSHING IS NOT PERMITTED.

MAKE ALL BOLTED DIAPHRAGM CONNECTIONS WITH 7/8" OR 1" ASTM F3125, GRADE A325 (TYPE 1) BOLTS. MECHANICALLY GALVANIZE BOLTS, HEAVY HEX NUTS, HARDENED WASHERS, AND DIRECT TENSION INDICATORS (DTI'S) IN ACCORDANCE WITH ASTM B 695 CLASS 50. FOR THE 1" BOLT ASSEMBLIES, GALVANIZING IN ACCORDANCE WITH AASHTO M 232 MAY BE SUBSTITUTED FOR MECHANICAL GALVANIZING.

SUBMIT SHOP PLANS FOR STEEL INTERMEDIATE DIAPHRAGMS IN ACCORDANCE WITH THE STANDARD SPECIFICATIONS.

AFTER INSTALLATION OF STEEL DIAPHRAGMS, REPAIR ALL DAMAGED AREAS OF THE GALVANIZED FINISH IN ACCORDANCE WITH ASTM A 780. USE PAINT METHOD TO REPAIR FINISH ON HARDWARE.


FORM BOLT HOLES IN PRESTRESSED CONCRETE BEAMS USING 2" INSIDE DIAMETER PIPE AND LEAVE PIPE IN PLACE AFTER FORMS ARE REMOVED.

TENSION BOLTS THROUGH THE BEAM WEB TO BE SNUG TIGHT AND THEN TURN THE BOLTS AN ADDITIONAL 1/4 TURN. PEEN THREADS ON ALL BOLTS INSTALLED THROUGH THE BEAM WEB. INSTALL ALL OTHER BOLTS USING A DTI AND HARDENED WASHER WITH EACH BOLT ASSEMBLY TO VERIFY PROPER TENSIONING.

DO NOT PLACE DECK SLAB UNTIL ALL INTERMEDIATE DIAPHRAGMS ARE PROPERLY INSTALLED AND TIGHTENED IN EACH SPAN WHERE DECK CONCRETE WILL BE PLACED DURING THE POUR.


LEAVE STEEL INTERMEDIATE DIAPHRAGMS IN PLACE AS A PERMANENT PART OF THE COMPLETED STRUCTURE.

INCLUDE ALL COST OF FURNISHING AND INSTALLING STEEL INTERMEDIATE DIAPHRAGM ASSEMBLIES IN THE UNIT PRICE BID FOR PRESTRESSED CONCRETE BEAMS.




ELEVATION

54" FLORIDA I-BEAM SHOWN, OTHERS SIMILAR.




18" CHANNEL

10" CHANNEL




6" CHANNEL

CHANNEL END DETAIL



SECTION A-A

LEFT SKEW SHOWN. RIGHT SKEW SIMILAR BY MIRROR ABOUT A LINE PARALLEL TO H.S. BOLT CENTERLINES.



10" OR 18" CHANNEL

6" CHANNEL

WEB PLATE DETAIL





PLATE WASHER DETAIL

USE 3 1/2" PLATE WASHER OVER ALL 1 5/8"x2 3/16" HOLES
USE 4" PLATE WASHER OVER ALL 1 1/8"x2 1/2" HOLES

BEAM	DIAPHRAGM	CONNECTION DIMENSIONS			
		A	B	C	D
36" F.I.B.	MC6X18	3 1/2"	N/A	1 3/4"	N/A
45" F.I.B.	MC10X22	10"	4"	3"	5"
54" F.I.B.	MC18X42.7	1'-6"	5"	4"	1'-1"
63" F.I.B.	MC18X42.7	1'-6"	5"	4"	1'-1"
72" F.I.B.	MC18X42.7	1'-6"	5"	4"	1'-1"



DIAPHRAGM FACE FOR 18" CHANNEL

DIAPHRAGM FACE FOR 10" CHANNEL

DIAPHRAGM FACE FOR 6" CHANNEL

WEB FACE FOR 10" OR 18" CHANNEL

WEB FACE FOR 6" CHANNEL

CORNER CLIP

SECTION B-B

CHANNEL CONNECTION BENT PLATE DETAILS

THIS DRAWING IS FURNISHED FOR INFORMATION ONLY. ALL DIMENSIONS SHOWN ARE SHEET SPECIFIC. ANY USE OF THIS DESIGN AND DRAWING, INCLUDING DIMENSIONS, MUST BE CHECKED BY THE USER'S ENGINEER TO ENSURE DESIGN IS ADEQUATE FOR THE INTENDED USE. ALL DRAWINGS MUST BE SIGNED AND SEALED BY A SOUTH CAROLINA REGISTERED PROFESSIONAL ENGINEER WHEN USED.

CONSULTANT NAME/LOGO

SOUTH CAROLINA DEPARTMENT OF TRANSPORTATION
FLORIDA I-BEAM STEEL INTERMEDIATE DIAPHRAGM DETAILS - ALT 2

COUNTY: ####

ROUTE: ####

DRAWING NUMBER: 704-FIB.STLINTDIA.CHAN.SKUNDER20

Dylan.Danks 6/21/2024 3:30:57 PM 704_StlIntDia.dgn

REV.	BY	CHK.	DATE	DESCRIPTION OF REVISION

REVIEWED	QUAN.	DR.	DMD	DEL	04-24
DES.	BY	CHK.	DATE		

NOTES:

PROVIDE STRUCTURAL STEEL SECTIONS, PLATES, AND PLATE WASHERS THAT CONFORM TO THE REQUIREMENTS OF AASHTO M 270, GRADE 50. GALVANIZE ALL COMPONENTS OF DIAPHRAGMS INCLUDING CONNECTION ANGLE OR CONNECTION PLATE AND PLATE WASHERS IN ACCORDANCE WITH AASHTO M 111. PERFORM GALVANIZING AFTER FABRICATION IS COMPLETED. ROUGHEN FAYING SURFACES OF BOLTED CONNECTIONS BY MEANS OF HAND-WIRE BRUSHING. POWER-WIRE BRUSHING IS NOT PERMITTED.

MAKE ALL BOLTED DIAPHRAGM CONNECTIONS WITH 7/8" OR 1" ASTM F3125, GRADE A325 (TYPE 1) BOLTS. MECHANICALLY GALVANIZE BOLTS, HEAVY HEX NUTS, HARDENED WASHERS, AND DIRECT TENSION INDICATORS (DTI'S) IN ACCORDANCE WITH ASTM B 695 CLASS 50. FOR THE 1" BOLT ASSEMBLIES, GALVANIZING IN ACCORDANCE WITH AASHTO M 232 MAY BE SUBSTITUTED FOR MECHANICAL GALVANIZING.

SUBMIT SHOP PLANS FOR STEEL INTERMEDIATE DIAPHRAGMS IN ACCORDANCE WITH THE STANDARD SPECIFICATIONS.

AFTER INSTALLATION OF STEEL DIAPHRAGMS, REPAIR ALL DAMAGED AREAS OF THE GALVANIZED FINISH IN ACCORDANCE WITH ASTM A 780. USE PAINT METHOD TO REPAIR FINISH ON HARDWARE.


FORM BOLT HOLES IN PRESTRESSED CONCRETE BEAMS USING 2" INSIDE DIAMETER PIPE AND LEAVE PIPE IN PLACE AFTER FORMS ARE REMOVED.

TENSION BOLTS THROUGH THE BEAM WEB TO BE SNUG TIGHT AND THEN TURN THE BOLTS AN ADDITIONAL 1/4 TURN. PEEN THREADS ON ALL BOLTS INSTALLED THROUGH THE BEAM WEB. INSTALL ALL OTHER BOLTS USING A DTI AND HARDENED WASHER WITH EACH BOLT ASSEMBLY TO VERIFY PROPER TENSIONING.

DO NOT PLACE DECK SLAB UNTIL ALL INTERMEDIATE DIAPHRAGMS ARE PROPERLY INSTALLED AND TIGHTENED IN EACH SPAN WHERE DECK CONCRETE WILL BE PLACED DURING THE POUR.


LEAVE STEEL INTERMEDIATE DIAPHRAGMS IN PLACE AS A PERMANENT PART OF THE COMPLETED STRUCTURE.

INCLUDE ALL COST OF FURNISHING AND INSTALLING STEEL INTERMEDIATE DIAPHRAGM ASSEMBLIES IN THE UNIT PRICE BID FOR PRESTRESSED CONCRETE BEAMS.




ELEVATION

54" FLORIDA I-BEAM SHOWN, OTHERS SIMILAR.




18" CHANNEL

10" CHANNEL




6" CHANNEL

CHANNEL END DETAIL



SECTION A-A

LEFT SKEW SHOWN. RIGHT SKEW SIMILAR BY MIRROR ABOUT A LINE PARALLEL TO H.S. BOLT CENTERLINES.



10" OR 18" CHANNEL

6" CHANNEL

WEB PLATE DETAIL




PLATE WASHER DETAIL

USE 3 1/2" PLATE WASHER OVER ALL 1 5/16\"/>

BEAM	DIAPHRAGM	CONNECTION DIMENSIONS			
		A	B	C	D
36" F.I.B.	MC6X18	3 1/2"	N/A	1 3/4"	N/A
45" F.I.B.	MC10X22	10"	4"	3"	5"
54" F.I.B.	MC18X42.7	1'-6"	5"	4"	1'-1"
63" F.I.B.	MC18X42.7	1'-6"	5"	4"	1'-1"
72" F.I.B.	MC18X42.7	1'-6"	5"	4"	1'-1"


CONSULTANT NAME/LOGO

SOUTH CAROLINA
DEPARTMENT OF TRANSPORTATION
**FLORIDA I-BEAM STEEL
INTERMEDIATE DIAPHRAGM
DETAILS - ALT 3**

COUNTY: ####

ROUTE: ####

DRAWING NUMBER: 704-FIB.STLINTDIA.CHAN.SKOVER20



DIAPHRAGM FACE FOR 18" CHANNEL

DIAPHRAGM FACE FOR 10" CHANNEL

DIAPHRAGM FACE FOR 6" CHANNEL

WEB FACE FOR 10" OR 18" CHANNEL

WEB FACE FOR 6" CHANNEL

CORNER CLIP


CHANNEL CONNECTION ANGLE DETAILS

THIS DRAWING IS FURNISHED FOR INFORMATION ONLY. ALL DIMENSIONS SHOWN ARE SHEET SPECIFIC. ANY USE OF THIS DESIGN AND DRAWING, INCLUDING DIMENSIONS, MUST BE CHECKED BY THE USER'S ENGINEER TO ENSURE DESIGN IS ADEQUATE FOR THE INTENDED USE. ALL DRAWINGS MUST BE SIGNED AND SEALED BY A SOUTH CAROLINA REGISTERED PROFESSIONAL ENGINEER WHEN USED.


Dylan.Danks 6/21/2024 3:30:58 PM 704_StlIntDia.dgn

REV.	BY	CHK.	DATE	DESCRIPTION OF REVISION


REVIEWED	QUAN.	DR.	DES.	BY	CHK.	DATE




ELEVATION
78" FLORIDA I-BEAM SHOWN, OTHERS SIMILAR.



WEB PLATE DETAIL



CROSS FRAME CONNECTION BENT PLATE DETAILS



NOTES:

PROVIDE STRUCTURAL STEEL SECTIONS, PLATES, AND PLATE WASHERS THAT CONFORM TO THE REQUIREMENTS OF AASHTO M 270, GRADE 50. GALVANIZE ALL COMPONENTS OF CROSS FRAMES INCLUDING CONNECTION PLATE AND PLATE WASHERS IN ACCORDANCE WITH AASHTO M 111. PERFORM GALVANIZING AFTER FABRICATION IS COMPLETED. ROUGHEN FAYING SURFACES OF BOLTED CONNECTIONS BY MEANS OF HAND-WIRE BRUSHING. POWER-WIRE BRUSHING IS NOT PERMITTED.

MAKE ALL BOLTED CROSS FRAME CONNECTIONS WITH 7/8" OR 1" ASTM F3125, GRADE A325 (TYPE 1) BOLTS. MECHANICALLY GALVANIZE BOLTS, HEAVY HEX NUTS, HARDENED WASHERS, AND DIRECT TENSION INDICATORS (DTI'S) IN ACCORDANCE WITH ASTM B 695 CLASS 50. FOR THE 1" BOLT ASSEMBLIES, GALVANIZING IN ACCORDANCE WITH AASHTO M 232 MAY BE SUBSTITUTED FOR MECHANICAL GALVANIZING.

SUBMIT SHOP PLANS FOR STEEL CROSS FRAMES IN ACCORDANCE WITH THE STANDARD SPECIFICATIONS.


AFTER INSTALLATION OF STEEL CROSS FRAMES, REPAIR ALL DAMAGED AREAS OF THE GALVANIZED FINISH IN ACCORDANCE WITH ASTM A 780. USE PAINT METHOD TO REPAIR FINISH ON HARDWARE.

FORM BOLT HOLES IN PRESTRESSED CONCRETE BEAMS USING 2" INSIDE DIAMETER PIPE AND LEAVE PIPE IN PLACE AFTER FORMS ARE REMOVED.

TENSION BOLTS THROUGH THE BEAM WEB TO BE SNUG TIGHT AND THEN TURN THE BOLTS AN ADDITIONAL 1/4 TURN. PEEN THREADS ON ALL BOLTS INSTALLED THROUGH THE BEAM WEB. INSTALL ALL OTHER BOLTS USING A DTI AND HARDENED WASHER WITH EACH BOLT ASSEMBLY TO VERIFY PROPER TENSIONING.

DO NOT PLACE DECK SLAB UNTIL ALL CROSS FRAMES ARE PROPERLY INSTALLED AND TIGHTENED IN EACH SPAN WHERE DECK CONCRETE WILL BE PLACED DURING THE POUR.

LEAVE STEEL CROSS FRAMES IN PLACE AS A PERMANENT PART OF THE COMPLETED STRUCTURE.



SECTION A-A






PLATE WASHER DETAIL
USE 3 1/2" PLATE WASHER OVER ALL 1 5/16"x2 3/16" HOLES
USE 4" PLATE WASHER OVER ALL 1 1/8"x2 1/2" HOLES



CROSS FRAME DETAILS

NOTE: BOLTS, NUTS, AND WASHERS NOT SHOWN FOR CLARITY.



CORNER CLIP DETAIL

BEAM	CONNECTION DIMENSIONS	
	A	B
78" F.I.B.	3'-4"	11"
84" F.I.B.	3'-10"	1'-1"
96" F.I.B.	4'-10"	1'-5"

SECTION B-B

THIS DRAWING IS FURNISHED FOR INFORMATION ONLY. ALL DIMENSIONS SHOWN ARE SHEET SPECIFIC. ANY USE OF THIS DESIGN AND DRAWING, INCLUDING DIMENSIONS, MUST BE CHECKED BY THE USER'S ENGINEER TO ENSURE DESIGN IS ADEQUATE FOR THE INTENDED USE. ALL DRAWINGS MUST BE SIGNED AND SEALED BY A SOUTH CAROLINA REGISTERED PROFESSIONAL ENGINEER WHEN USED.

CONSULTANT NAME/LOGO

SOUTH CAROLINA
DEPARTMENT OF TRANSPORTATION


**FLORIDA I-BEAM STEEL
INTERMEDIATE CROSS FRAME
DETAILS - ALT 1**

COUNTY: #### ROUTE: ####


REVIEWED	BY	CHK.	DATE
QUAN.	DMD	AEL	04-24
DR.			
DES.			

REV.	BY	CHK.	DATE	DESCRIPTION OF REVISION


Dylan.Danks 6/21/2024 3:30:59 PM 704_STLINTDia.dgn




ELEVATION
78" FLORIDA I-BEAM SHOWN, OTHERS SIMILAR.



WEB PLATE DETAIL




WEB FACE



DIAPHRAGM FACE - PL 1

DIAPHRAGM FACE - PL 2

CROSS FRAME CONNECTION BENT PLATE DETAILS



SECTION A-A

LEFT SKEW SHOWN. RIGHT SKEW SIMILAR BY MIRROR ABOUT A LINE PARALLEL TO H.S. BOLT CENTERLINES.






PLATE WASHER DETAIL

USE 3 1/2" PLATE WASHER OVER ALL 1 5/16" x 2 3/16" HOLES
USE 4" PLATE WASHER OVER ALL 1 1/8" x 2 1/2" HOLES



CROSS FRAME DETAILS

NOTE: BOLTS, NUTS, AND WASHERS NOT SHOWN FOR CLARITY.



CORNER CLIP DETAIL

NOTES:
PROVIDE STRUCTURAL STEEL SECTIONS, PLATES, AND PLATE WASHERS THAT CONFORM TO THE REQUIREMENTS OF AASHTO M 270, GRADE 50. GALVANIZE ALL COMPONENTS OF CROSS FRAMES INCLUDING CONNECTION PLATE AND PLATE WASHERS IN ACCORDANCE WITH AASHTO M 111. PERFORM GALVANIZING AFTER FABRICATION IS COMPLETED. ROUGHEN FAYING SURFACES OF BOLTED CONNECTIONS BY MEANS OF HAND-WIRE BRUSHING. POWER-WIRE BRUSHING IS NOT PERMITTED.

MAKE ALL BOLTED CROSS FRAME CONNECTIONS WITH 7/8" OR 1" ASTM F3125, GRADE A325 (TYPE 1) BOLTS. MECHANICALLY GALVANIZE BOLTS, HEAVY HEX NUTS, HARDENED WASHERS, AND DIRECT TENSION INDICATORS (DTI'S) IN ACCORDANCE WITH ASTM B 695 CLASS 50. FOR THE 1" BOLT ASSEMBLIES, GALVANIZING IN ACCORDANCE WITH AASHTO M 232 MAY BE SUBSTITUTED FOR MECHANICAL GALVANIZING.

SUBMIT SHOP PLANS FOR STEEL CROSS FRAMES IN ACCORDANCE WITH THE STANDARD SPECIFICATIONS.

AFTER INSTALLATION OF STEEL CROSS FRAMES, REPAIR ALL DAMAGED AREAS OF THE GALVANIZED FINISH IN ACCORDANCE WITH ASTM A 780. USE PAINT METHOD TO REPAIR FINISH ON HARDWARE.

FORM BOLT HOLES IN PRESTRESSED CONCRETE BEAMS USING 2" INSIDE DIAMETER PIPE AND LEAVE PIPE IN PLACE AFTER FORMS ARE REMOVED.

TENSION BOLTS THROUGH THE BEAM WEB TO BE SNUG TIGHT AND THEN TURN THE BOLTS AN ADDITIONAL 1/4 TURN. PEEN THREADS ON ALL BOLTS INSTALLED THROUGH THE BEAM WEB. INSTALL ALL OTHER BOLTS USING A DTI AND HARDENED WASHER WITH EACH BOLT ASSEMBLY TO VERIFY PROPER TENSIONING.

DO NOT PLACE DECK SLAB UNTIL ALL CROSS FRAMES ARE PROPERLY INSTALLED AND TIGHTENED IN EACH SPAN WHERE DECK CONCRETE WILL BE PLACED DURING THE POUR.

LEAVE STEEL CROSS FRAMES IN PLACE AS A PERMANENT PART OF THE COMPLETED STRUCTURE.

BEAM	CONNECTION DIMENSIONS	
	A	B
78" F.I.B.	3'-4"	11"
84" F.I.B.	3'-10"	1'-1"
96" F.I.B.	4'-10"	1'-5"

CONSULTANT NAME/LOGO

SOUTH CAROLINA
DEPARTMENT OF TRANSPORTATION
**FLORIDA I-BEAM STEEL
INTERMEDIATE CROSS FRAME
DETAILS - ALT 2**


THIS DRAWING IS FURNISHED FOR INFORMATION ONLY. ALL DIMENSIONS SHOWN ARE SHEET SPECIFIC. ANY USE OF THIS DESIGN AND DRAWING, INCLUDING DIMENSIONS, MUST BE CHECKED BY THE USER'S ENGINEER TO ENSURE DESIGN IS ADEQUATE FOR THE INTENDED USE. ALL DRAWINGS MUST BE SIGNED AND SEALED BY A SOUTH CAROLINA REGISTERED PROFESSIONAL ENGINEER WHEN USED.

COUNTY: #### ROUTE: ####

DRAWING NUMBER: 704-FIB.STLINTDIA.CROSS.SKUNDER20


REVIEWED	QUAN.	DR.	DES.	BY	CHK.	DATE	DESCRIPTION OF REVISION

Dylan.Danks 6/21/2024 3:31:00 PM 704_StlIntDia.dgn




ELEVATION


78" FLORIDA I-BEAM SHOWN, OTHERS SIMILAR.



WEB PLATE DETAIL




WEB FACE



DIAPHRAGM FACE - PL 1

DIAPHRAGM FACE - PL 2



SECTION A-A

LEFT SKEW SHOWN. RIGHT SKEW SIMILAR BY MIRROR ABOUT A LINE PARALLEL TO H.S. BOLT CENTERLINES.






PLATE WASHER DETAIL

USE 3 1/2" PLATE WASHER OVER ALL 1 5/16" x 2 3/16" HOLES
USE 4" PLATE WASHER OVER ALL 1 1/8" x 2 1/2" HOLES




CROSS FRAME DETAILS

NOTE: BOLTS, NUTS, AND WASHERS NOT SHOWN FOR CLARITY.



CORNER CLIP DETAIL



SECTION B-B

NOTES:

PROVIDE STRUCTURAL STEEL SECTIONS, PLATES, AND PLATE WASHERS THAT CONFORM TO THE REQUIREMENTS OF AASHTO M 270, GRADE 50. GALVANIZE ALL COMPONENTS OF CROSS FRAMES INCLUDING CONNECTION PLATE AND PLATE WASHERS IN ACCORDANCE WITH AASHTO M 111. PERFORM GALVANIZING AFTER FABRICATION IS COMPLETED. ROUGHEN FAYING SURFACES OF BOLTED CONNECTIONS BY MEANS OF HAND-WIRE BRUSHING. POWER-WIRE BRUSHING IS NOT PERMITTED.

MAKE ALL BOLTED CROSS FRAME CONNECTIONS WITH 7/8" OR 1" ASTM F3125, GRADE A325 (TYPE 1) BOLTS. MECHANICALLY GALVANIZE BOLTS, HEAVY HEX NUTS, HARDENED WASHERS, AND DIRECT TENSION INDICATORS (DTI'S) IN ACCORDANCE WITH ASTM B 695 CLASS 50. FOR THE 1" BOLT ASSEMBLIES, GALVANIZING IN ACCORDANCE WITH AASHTO M 232 MAY BE SUBSTITUTED FOR MECHANICAL GALVANIZING.

SUBMIT SHOP PLANS FOR STEEL CROSS FRAMES IN ACCORDANCE WITH THE STANDARD SPECIFICATIONS.

AFTER INSTALLATION OF STEEL CROSS FRAMES, REPAIR ALL DAMAGED AREAS OF THE GALVANIZED FINISH IN ACCORDANCE WITH ASTM A 780. USE PAINT METHOD TO REPAIR FINISH ON HARDWARE.

FORM BOLT HOLES IN PRESTRESSED CONCRETE BEAMS USING 2" INSIDE DIAMETER PIPE AND LEAVE PIPE IN PLACE AFTER FORMS ARE REMOVED.

TENSION BOLTS THROUGH THE BEAM WEB TO BE SNUG TIGHT AND THEN TURN THE BOLTS AN ADDITIONAL 1/4 TURN. PEEN THREADS ON ALL BOLTS INSTALLED THROUGH THE BEAM WEB. INSTALL ALL OTHER BOLTS USING A DTI AND HARDENED WASHER WITH EACH BOLT ASSEMBLY TO VERIFY PROPER TENSIONING.

DO NOT PLACE DECK SLAB UNTIL ALL CROSS FRAMES ARE PROPERLY INSTALLED AND TIGHTENED IN EACH SPAN WHERE DECK CONCRETE WILL BE PLACED DURING THE POUR.

LEAVE STEEL CROSS FRAMES IN PLACE AS A PERMANENT PART OF THE COMPLETED STRUCTURE.

BEAM	CONNECTION DIMENSIONS	
	A	B
78" F.I.B.	3'-4"	11"
84" F.I.B.	3'-10"	1'-1"
96" F.I.B.	4'-10"	1'-5"

CONSULTANT NAME/LOGO

SOUTH CAROLINA DEPARTMENT OF TRANSPORTATION

FLORIDA I-BEAM STEEL INTERMEDIATE CROSS FRAME DETAILS - ALT 3

COUNTY: ####

ROUTE: ####

DRAWING NUMBER: 704-FIB.STLINTDIA.CROSS.SKOVER20

THIS DRAWING IS FURNISHED FOR INFORMATION ONLY. ALL DIMENSIONS SHOWN ARE SHEET SPECIFIC. ANY USE OF THIS DESIGN AND DRAWING, INCLUDING DIMENSIONS, MUST BE CHECKED BY THE USER'S ENGINEER TO ENSURE DESIGN IS ADEQUATE FOR THE INTENDED USE. ALL DRAWINGS MUST BE SIGNED AND SEALED BY A SOUTH CAROLINA REGISTERED PROFESSIONAL ENGINEER WHEN USED.

REV.	BY	CHK.	DATE	DESCRIPTION OF REVISION

REVIEWED	BY	CHK.	DATE
QUAN.	DMD	AEL	04-24
DR.			
DES.			

Dylan.Danks 6/21/2024 3:31:01 PM 704_STLINTDia.dgn